

POWERSONIC 12 VOLT LEAD ACID BATTERIES



Part Number	Volts	Capacity 20Hr. Rate	Dimensions (Inches)			Weight (Lbs)	Cross Reference	Termination
			Length	Width	Height Inc. Term			
LEAD-12-0.8PS	12	0.8	3.8	1.0	2.4	0.8	PS-1208	WIRE AND CONN
LEAD-12-1.2PS	12	1.2	3.8	1.7	2.0	1.3	PS-1212	.187 TAB
LEAD-12-2PS	12	2.2	7.0	1.3	2.4	1.9	PS-1220	.187 TAB
LEAD-12-2.8PS	12	2.8	5.2	1.3	3.8	2.3	PS-1228	.187 TAB
LEAD-12-2.9PS	12	2.9	7.0	1.3	2.4	2.2	PS-1229	.187 TAB
LEAD-12-3PS	12	3.0	5.3	2.6	2.4	2.6	PS-1230	.187 TAB
LEAD-12-4PS	N/A – USE LEAD-12-5PS						PS-1242	
LEAD-12-5PS	12	5.0	3.5	2.8	4.0	3.8	PS-1250-F1	.187 TAB
LEAD-12-5PS-250	12	5.0	3.5	2.8	4.0	3.8	PS-1250-F2	.250 TAB
LEAD-12-5.2PS	N/A – USE LEAD-12-5PS-250						PS-1252	
LEAD-12-6.5PS	N/A – USE LEAD-12-7PS						PS-1265	
LEAD-12-7PS	12	7.0	6.0	2.6	3.7	5.7	PS-1270	.187 TAB
LEAD-12-8PSL	12	8.0	7.7	2.2	4.7	6.7	PS-1282L	.187 TAB
LEAD-12-8PSS	12	8.0	3.9	4.4	4.7	6.7	PS-1282S	.187 TAB
LEAD-12-10PS	12	12.0	6.0	4.0	3.7	9.2	PS-12100-F2	.250 TAB
LEAD-12-12PS	12	12.0	6.0	3.9	3.7	10.3	PS-12120	.250 TAB
LEAD-12-18T-PS	12	18.0	7.1	3.0	6.6	13.1	PS-12180-F2	.250 TAB
LEAD-12-18B-PS	12	18.0	7.1	3.0	6.6	13.1	PS-12180-NB	NUT & BOLT
LEAD-12-26B-PS	12	26.0	6.9	6.5	4.9	18.7	PS-12260-NB	NUT & BOLT
LEAD-12-26T-PS	12	26.0	6.9	6.5	4.9	18.7	PS-12260-F2	.250 TAB
LEAD-12-28B-PS	12	28.0	6.5	4.9	6.9	19.4	PS-12280	NUT & BOLT
LEAD-12-33PS	12	33.0	7.7	5.2	6.1	26.5	PS-12330-NB	NUT & BOLT
LEAD-12-40PS	12	40.0	7.8	6.5	6.7	30.9	PS-12400	NUT & BOLT
LEAD-12-55PS	12	55.0	9.5	5.5	8.1	41.1	PS-12550-NB	NUT & BOLT
LEAD-12-60PS	N/A – USE LEAD-12-75PS						PS-12600	
LEAD-12-75PS	12	75.0	10.3	6.6	8.2	55.1	PS-12750-NB	NUT & BOLT
LEAD-12-80PS	N/A – USE LEAD-12-75PS (NOTE SIZE AND MAH)						PS-12800	
LEAD-12-100PS	12	100.0	13.1	6.9	9.4	70.5	PS-121000-NB	NUT & BOLT

NOTES

LEAD ACID