


Model #: BP36V42-3U

BP36V42-3U - External Battery Pack for UPS System



• Extends runtime of select compatible Tripp Lite UPS Systems with 36V DC

- Simple installation; 3U rackmount, tower and stack adaptable
- 2-year warranty

external battery connector

Highlights



Description

BP36V42-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 3 rack spaces (3U). Includes heavy gauge cabling with high current DC connector for simple installation. Additional output connector allows multiple BP36V42-3U battery packs to be daisy-chained to the UPS for even longer extended run operation.

Compatible UPS systems - SMART1500RMXL2Ua, SMX1500RTXL2U and other Tripp Lite UPS systems that specify the use of this battery pack.

Applications

• Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- External battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Attractive all-black color scheme
- Additional output connector allows multiple battery packs to be daisy-chained to the UPS for even longer extended run operation
- 2 year warranty

Specifications

BATTERY

| Expandable battery runtime | Includes a second input/output connector to daisy-chain multiple battery packs | | |
|---|--|--|--|
| DC system voltage (VDC) | 36 | | |
| Connects to UPS via | Detachable cable with UPS specific DC connector (36 in length, 6 gauge) | | |
| Typical battery lifespan | 4-6 years typical (North America) | | |
| PHYSICAL | | | |
| Shipping weight (lbs) | 165.35 | | |
| Shipping weight (kg) | 75.1 | | |
| Unit Dimensions (HWD/in) | 5.25 x 17.5 x 25 | | |
| Unit Dimensions (HWD/cm) | 13.3 x 44.45 x 63.5 | | |
| Shipping Dimensions (HWD/in) | 11.25 x 23 x 31.5 | | |
| Shipping Dimensions (HWD/cm) | 28.6 x 58.42 x 80.01 | | |
| Unit weight (Ibs) | 127.87 | | |
| Unit weight (kg) | 58.1 | | |
| Material of construction | Steel | | |
| Form factors supported | 3U rack/tower | | |
| WARRANTY | | | |
| Product Warranty Period (U.S., Canada & Puerto Rico) | 2-year limited warranty | | |
| Optional Coverage | 3 and 5 year warranty extensions available | | |

Related Items

Optional Products

| Product Type | Related Model | Description | Qty. |
|--------------------------|---------------|--|------|
| Extended Warranties | WEXT3-BP36V | 3-Year Extended Warranty - For All 36V Battery Packs | - |
| Extended Warranties | WEXT5-BP36V | 5-Year Extended Warranty - For All 36V Battery Packs | - |
| Tower Stands | 2-9USTAND | Enables Tower Placement of Rackmount UPS Systems | - |
| Rackmount/Wallmount Kits | 2POSTRMKITHD | Enables 2-Post Rackmount Installation of 3U and Larger UPS, Transformer and Battery Pack Components | - |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3018.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.