



# Solar Charger Controller CC-25000

- Perfect match for solar panels generating up to 25A of current.
- It works with all 12V battery systems and its intelligent PWM (Pulse Width Modulation) feature ensures batteries reach max. capacity.
- Multiple LED indicators show the charge status and battery condition
- Nominal Voltage: 12V / 24 V
- Max Array Voltage (Voc) 30V / 50 V
- Continuous Charging Current: 25A
- Temperature Range: -40 to 50 °C (-40 to 122 °F) For indoor use only



- Avoids Solar panel overcharging of battery systems
- Integrated screw terminal connections for quick and easy installation.
- Simple to follow logos for worry free battery and Solar panel connection.
- Built in Surge protection and automatic reset for battery protection and continuous hassle free operation."
- Reverse polarity protection, battery will not be damaged if Negative and Positive wires are switched."
- Reverse current protection, blocking diode prevents your batteries from draining at night.
- Low self power consumption so that more power will be stored in your battery.

**SUNSEI®**, My Solar Lifestyle

USA

CANADA

EUROPE

ASIA

AUSTRALIA



ICPSOLAR.COM

| SPECIFICATIONS                     |   |
|------------------------------------|---|
| Model number                       | CC-25000  |
| Item number                        | 11101   |
| UPC Code                           | 7 75540 11101 0                                   |
| Maximum Current                    | 25 A  |
| Case protection                    | IP22  |
| Warranty                           | 2 years warranty                                  |
| Certification                      | CE  |
| THE BOX INCLUDES                   |   |
| 1 Charge controller CC-25000       |   |
| 1 Multi-Lingual instruction manual |   |
| WEIGHTS AND DIMENSIONS             |   |
| Dimensions                         | 4" x 3 1/8" x 1 3/8"<br>10.16cm x 7.95cm x 3.51cm |
| Weight                             | 1 lbs<br>0.45 kg                                  |