

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

REVISIONS		DOC. NO.	SPC-F005		* Effective: 12/21/98		* DCP No. 680	
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRD	DATE
796	A	RELEASED	HO	3/28/02	JWM	3/28/02	DJC	3/28/02



Formulated to prolong tip life in the harsh soldering environments of rosin, no-clean and water soluble fluxes. Flux usage allows oxide build-up on tip, causing poor thermal transfer and dewetting of the tip surface. Use on standard tips.

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, WE MAKE NO WARRANTY, REPRESENTATION OR STATEMENT OF MERCHANTABILITY INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.



SPC TECHNOLOGY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	HISHAM ODISH	DATE:	3/28/02
CHECKED BY:	JEFF MCVICKER	DATE:	3/28/02
APPROVED BY:	DANIEL CAREY	DATE:	3/28/02

DRAWING TITLE:				1/2 OZ. LEAD FREE TIP TINNER			
SIZE	DWG. NO.	ELECTRONIC FILE	REV	SCALE:	NTS	U.O.M.: INCHES [mm]	SHEET:
A	1471	10N694.DWG	A				1 OF 1