




ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.


SPC-F005.DWG

		REVISIONS	DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398							
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD DATE		APPRVD	DATE		
1891	Α	RELEASED	EO	06/27/06	YA	7/25/06	но	7/25/06		










#4-40 UNC Hexscrew



- SPECIFICATIONS:

 CURRENT RATING: 3 AMP

 Insulator: PBT Glass fibre reinforced UL94V-0
- Contact: Brass

- Contact: Brass
 Contact: Plated: Gold plated over Nickel
 Shell: Tin Plated Shell
 Dielectric Strength: 1000 VAC for one Minute
 Insulator Resistance: 1000 Megohm min at 500 VDC
 Temperature: -55°C to +105°C

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED
HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE
BELIEVE TO BE ACCURATE AND RELIABLE. SINCE
CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE
USER SHALL DETERMINE THE SUITABLITY OF THE PRODUCT
FOR THE INTENDED USE AND ASSUME ALL RISK AND
LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:	DRAWN BY:					
Unless Otherwise	EKLAS ODISH					
Specified	CHECKED BY:					
.X ±0.2 [0.008]	YILMAZ AKYO					
XX ±0.10 [0.004]	APPROVED B					
	HISHAM ODIS					

DRAWN BY:	DATE:	DRAW	ING TITLE:		
EKLAS ODISH	06/27/06	l	₋ow Pro		
CHECKED BY:	DATE:	SIZE	DWG. NO		
YILMAZ AKYONDEM	7/25/06	Α			
APPROVED BY:	DATE:				
HISHAM ODISH	7/25/06	SCAL	E: NTS		

:	DRAW												
06	L	-ow	Prof	Gend	er	Changer,	DB	15 F	Pin	Male	/M	ale)
:	SIZE DWG. NO.							ELECTRONIC FILE					REV
26	A SPC1					19757 84			84K8523.DWG			Α	
: 06	SCALE: NTS				U.O.M.: mm [INCHES]			Sŀ	HEET:	1	OF	1	