



REVISIONS			
SYM	ZONE	ECN, ERN NO.	DATE
B		PRODUCT DRAWING	03/09/11
			ATP

THIS IS A CAD DRAWING. DO NOT MANUALLY REVISE.

4-40 UNC (MTG. CODE 4) OR
M3 X 0.5 (MTG. CODE 6)
SCREW INSTALLED.

THREADED HEX NUT
.187[4.76] ACROSS FLATS
SUPPLIED BULK PACKED

PLUG

RECEPTACLE

ORDERING CODE:

PART NUMBER F C C 5 7 - 0 9 5 0 - 4 1 0

- SERIES _____
- STYLE _____
- 09=ADAPTER _____
- NUMBER OF CONTACTS _____
- MODIFIER _____
- 0=STANDARD _____
- MOUNTING OPTION _____
- 4=#4-40 UNC THREADED SCREW & HEX NUT _____
- 6=M3 - 0.5 THREADED SCREW & HEX NUT _____

- MODIFIER (0=STANDARD)
- CAPACITANCE
- D=50 pF
- B=100 pF
- O=180 pF
- 1=470 pF
- 3=820 pF
- 5=1000 pF
- 7=1200 pF
- E=2200 pF
- 9=5600 pF
- 8=47000 pF
- REFER TO AMPHENOL CATALOGUE FOR FILTER PERFORMANCE CHARACTERISTICS

MATERIALS:

- SHELL:** ALUMINUM DIECAST, TIN PLATED.
- CONTACTS:** PHOSPHOR BRONZE, 30 MICROINCHES [0.76 MICRONS] OF GOLD PLATED OVER NICKEL ON CONTACT MATING AREAS.
- INSERT:** HIGH STRENGTH THERMOPLASTIC POLYESTER FLAMMABILITY RATING UL 94V-0, BLACK.

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.

MATERIAL -----	DRAWN <u>I.ESSAJEE</u>	DATE <u>00/01/05</u>	Amphenol Canada Corp.	
	DESIGNED _____	_____		
FINISH -----	CHECKED <u>K.LAMBIE</u>	DATE <u>00/01/13</u>	TITLE FCC57 FILTERED MICRO-RIBBON CONNECTOR, PLUG/RECEPTACLE ADAPTER, 50 SIZE, WITH LATCH SPRINGS & MOUNTING HARDWARE	
	I. E. APPRD. _____	_____		
	Q. A. APPRD. _____	_____	DWG. APPRD. _____	DWG. NO. <u>P-FCC57-09500-XX0</u>
	ENG. REL. NO. _____	REF. <u>EAR C10929</u>	SCALE <u>2/1</u>	WT. _____
	DIMENSIONS ARE IN INCHES [mm]	CODE ID. NO. <u>03554</u>	SURF. _____	SHEET <u>1</u> of <u>1</u>