

5
4
3
2
1

Mating face according to : MIL -C-24308 / DIN 41652 / 75301-802

No.1 Contact

$\phi 3,05 \pm 0,1$

PCB

4 min

Assembly position

SPECIFICATION

| | |
|-----------------------|------------|
| Mating Cycles | 200 |
| Capacitance | 3900pf±20% |
| Working Voltage | 100v |
| Current Rating | 7.5A |
| Insulation Resistance | >1GΩ |

| FREQUENCY (MHz) | ATTENUATION (dB) |
|-----------------|------------------|
| 5 | 6dB |
| 10 | 11dB |
| 50 | 25dB |
| 100 | 35dB |
| 500 | 35dB |
| 1000 | 32dB |

PCB Layout Component side

No.1 contact

No.13 contact

No.25 contact

| | | | | | |
|--|--|--|---------|----------|------|
| | | | | Dot. | Name |
| | | | Detail. | 8-JUL-02 | CV |
| | | | Insp. | | |
| | | | Stand. | | |

| | |
|--|--|
| | |
| <small>All Dim. in mm Orig. Size DIN A 4</small> | |

| | | |
|--|--|---|
| D-Sub, male, straight, 25 Poles, with turned solder pin and hole | | <small>Mod./Tab/ Scale</small> 1.5:1 |
| TB 09643227240 | | <small>Blatt / Page</small> 1 / 1 |

| | | | | | |
|---------------------|---------------------|---------------------|--|--|--|
| 31058 | 8-JUL-02 | CV | | | |
| <small>Mod.</small> | <small>Dat.</small> | <small>Name</small> | | | |

| | | |
|--------------------------------------|--|--|
| HARTING EURL F-95972 Paris | | |
| <small>Sub.</small> | | |