


Specifications:
 Current rating:3.0A AC,DC
 Voltage rating:250V AC,DC
 Temperature range:-40°C ~ +85°C
 Contact resistance:30mohm max.
 Insulation resistance: 5,000Mohm min.
 Withstanding voltage:1,000V AC/Minute
 Materials:
 Insulator:High temp.plastic (UL94V-0)
 Contact:Copper alloy Nickel Undercoated,
 Selective Gold plated
 Finish:Metal Iron with Tin plated
 How To Order
 5501-XXPA-XX-XX-XXF1




- Lead Free
- Blank:White(Standard Color)
- BK:Black; BU:Blue
- Blank:Standard type
- CS:Rear Rivet
- CC:Front Rivet
- 01:Full Gold Plated
- 02:Selective Gold
- PA:Stamp Pin Male
- No.Of Positions

Pos	A	B	C	D	E
9	16.92	24.99	30.81	8.38	12.50
15	25.25	33.32	39.14	8.38	12.50
25	38.96	47.04	53.04	8.38	12.50
37	55.42	63.50	69.32	8.38	12.50
50	52.81	61.11	66.93	11.07	15.37

RoHS Compliant

F			
E			
D			
C			
B			
A	19-Aug-2005	(PC0052)	Cel King
REV	DATE	FILE	BY

DRAWN: Cel King	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15
CHECKED: JEREMY LIU	UNIT: MM
APPROVAL: MIKE WU	SCALE: 1:1
	SHEET: 1 / 1
	PROJECTION:

 繼德工業股份有限公司
Neltron Industrial Co., Ltd.

DESCRIPTION:
D-SUB Solder Male Stamp Pin Type

PART NO:
5501-XXPA-XX-XX-XXF1

SIZE	A4
------	-----------