


RECOMMENDED P.C. BOARD HOLE-LAYOUT



DO NOT SCALE METRIC THIRD ANGLE PROJECTION

ITEM NR.	DESCRIPTION OF ACCESSORY	2	2	2	2	2	2
5	BUSHING WITH THROUGH-HOLE 3,1 DIA.						
5	BUSHING WITH THREAD 4-40 UNC						
5	BUSHING WITH THREAD M3						
4	FEMALE SCREWLOCK WITH THREAD 4-40 UNC						
4	FEMALE SCREWLOCK WITH THREAD M3						
6	BOARDLOCK						

HOW TO ORDER:
 9 POS.-----> Z-338313-Y
 PREFIX FOR ACCESSORIES
 BASIC PARTNR.
 SUFFIX FOR PLATING

PLATING SUFFIX:
 GOLD OVER NICKEL AS PER PERFORMANCE LEVEL 2 (DIN 41652) } -Y = -2
 SOLDER-PART : 2,5µm BRIGHT SnPb

△ GROOVE INDICATES VERSION WITH 4-40 UNC INNER THREAD; WITHOUT GROOVE INDICATES VERSION WITH M3 INNER THREAD.
 △ CAVITY IDENTIFICATION AT FRONT SIDE ONLY.
 △ PARTNUMBER AND DATE CODE.
 4 WHEN BOARDLOCKS ARE USED, CONNECTOR CAN BE USED FOR PCB THICKNESS OF 1,6 mm ONLY.

ITEM_NRS./MATERIAL :

① SHELL	= BRIGHT TINPLATED STEEL
② HOUSING	= GLASSFILLED POLYESTER, COLOR : BLACK
③ CONTACTS	= PHOSPHORBRONZE (PLATING : SEE TABLE ABOVE)
④ FEMALE SCREWLOCK	= TINPLATED STEEL (INNER THREAD 4-40 UNC OR M3)
⑤ BUSHING	= TINPLATED STEEL (INNER THREAD 4-40 UNC OR M3 OR 3,1 DIA. THROUGH-HOLE)
⑥ BOARDLOCK	= TINPLATED PHOSPHORBRONZE
⑦ STAND OFF	= ULTRAMID V0 COLOR : BLACK

-		-		-		CUSTOMER DRAWING FOR REFERENCE ONLY WILL NOT BE UPDATED	
D		EH-1417-99	P.W.	W.G.	18-02-00	© COPYRIGHT 19-- BY AMP-HOLLAND B.V. ALL INTERNATIONAL RIGHTS RESERVED.AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN AND/OR PATENTS PENDING THIS DRAWING IS UNPUBLISHED	
C		EH-0033-99	D.K.	W.S.	21 JUN 99	RELEASED FOR PUBLICATION	
B		EH-1385-98	W.S.	W.S.	04-09-98	AMP-HOLLAND B.V. 's-Hertogenbosch, The Netherlands.	
A		EH-1390-97	J.V.L.	C.S.	16-09-98	NAME	
0		EH-0670-97	J.V.L.	C.S.	01-07-97	HD-20 SIZE 1 VERTICAL+ RECEPTACLE HEADER; WITH SOLDER CONTACTS	
LTR.		REVISION RECORD		DR.		CHK.	DATE
DR.		J.V.A.E.R.T.	CHK.	C.S.B.S.A.	APP.	E.L.E.U.N.S.	DATE: 01-07-97 DATE: 09-09-97
DATE:		01-07-97		DATE:		09-09-97	
DWG.No.		C-338313		REV.LTR.		D 1 of 1	
SHEET		1		of		1	
A2							