



# Twist-Lock® Devices

## 30 Ampere, 3Ø Y 120/208, 277/480 and 347/600 Volts AC

4 Pole, 4 Wire Non-Grounding

### Insulgrip® Plugs, Flanged Inlets, Connector Bodies and Receptacles



**HBL2751**

**IP20**  
SUITABILITY



**30A 3ØY**  
**120/208V AC**  
NEMA L18-30P  
UL Listed  
3 HP



**30A 3ØY**  
**277/480V AC**  
NEMA L19-30P  
UL Listed  
10 HP




**30A 3ØY**  
**347/600V AC**  
NEMA L20-30P  
UL Listed

## Plugs

Description	Cord Dia.	Catalog Numbers		
Black and white nylon.	.35"-1.15" (9-29)	<b>HBL2751</b>	<b>HBL2761</b>	<b>HBL2771</b>

Accessories on page B-53.



**HBL2755**

## Flanged Inlets

Description	Catalog Numbers		
Nylon casing, back wired.	<b>HBL2755</b>	<b>HBL2765</b>	<b>HBL2775</b>

Accessories on page B-52.



**HBL2753**

**IP20**  
SUITABILITY



**30A 3ØY**  
**120/208V AC**  
NEMA L18-30R  
UL Listed  
3 HP



**30A 3ØY**  
**277/480V AC**  
NEMA L19-30R  
UL Listed  
10 HP




**30A 3ØY**  
**347/600V AC**  
NEMA L20-30R  
UL Listed

## Connector Bodies

Description	Cord Dia.	Catalog Numbers		
Black and white nylon.	.35"-1.15" (9-29)	<b>HBL2753</b>	<b>HBL2763</b>	<b>HBL2773</b>

Accessories on page B-53.



**HBL2750**

## Single Flush Receptacles, Back and Side Wired


Description	Catalog Numbers		
Black nylon face.	<b>HBL2750</b>	<b>HBL2760</b>	<b>HBL2770</b>

Accessories on page B-52.

## Flanged Receptacles

Description	Catalog Numbers		
Nylon casing, back wired.	<b>HBL2756</b>	<b>HBL2766</b>	<b>HBL2776</b>

Accessories on page B-52.



**HBL2756**

Note: For technical information on Twist-Lock® Devices see page B-69.

