Marine Products **15 Ampere, 125V AC** ^{2 Pole 3 Wire} **TWIST-LOCK® Locking Type Devices**

(ኪ) 🚯

Description

IP20 SUITABILITY.

IP20 SUITABILITY.

IP55 SUITABILITY.

adapters. IP20 SUITABILITY.

Notes: *Not shown.

and stainless steel casing. IP20 SUITABILITY.

and stainless steel casing. IP20 SUITABILITY.

+ Boots are not UL listable.

strain relief.

15A 125V AC Twist-Lock Devices

Yellow duplex receptacle has heat resistant body. IP20 suitABILITY. HBL47CM00

Short yellow Seal-Tite[®] cover for weatherproofing #HBL47CM20C HBL60CM23+ Insulgrip[®] plug when used with receptacles or connector bodies.

Yellow Valox® spring-loaded lift cover plate for weatherproofing

duplex receptacles. Stainless steel screws and neoprene gasket included for mounting to FS/FD type weatherproof boxes.

Same as #HBL52CM21 except white in color. IP20 suitability.

Same as #HBL52CM21 except gray in color. IP20 suitability.

Same as #HBL52CM22 except gray in color. IP20 suitability.

Also can be used to weatherproof #HBL47CM29C Insulgrip® connector body when used with #HBL47CM16 flanged inlet.

Yellow Insulgrip[®] connector body has rugged nylon housing and detachable cord grip with range of .296"-.687" (7.5-17.4) that

utilizes a unique offset jaws arrangement to provide secure

Yellow Seal-Tite[®] cover for weatherproofing #HBL47CM29C

Insulgrip® connector body when used on extension cords and

Panel mount flanged outlet has heat resistant melamine interior

Panel mount flanged inlet has heat resistant melamine interior

Three conductor, #14 AWG type STW, yellow PVC jacketed portable cord has jute fillers for added flexibility and is ideal for

making cable sets, extension cords and adapters as it will not mark the boat's deck. Available in 250' (76.2m) lengths only.

Valox ® is a registered trademark of General Electric Company.

Yellow Insulgrip[®] plug has rugged nylon housing and detachable cord grip with range of .296"-.687" (7.5-17.4) that utilizes a unique offset jaws arrangement to provide secure strain relief.

Same as #HBL52CM21 except for mounting to standard boxes.



HBL47CM00



HBL52CM21 HBL52CM21W



HBL47CM20C



HBL60CM23



HBL47CM29C



HBL60CM24



HBL47CM15



15A 125V NEMA L5-15R

Catalog Numbers

HBL52CM21

HBL52CM21W

HBL52CM22*

HBL47CM20C

HBL47CM29C

HBL60CM24+

HBL47CM15

HBL47CM16

YC314250*

HBL5221

HBL5222*

HBL47CM16

2P 3W, 15A, 125V, TWIST-LOCK[®] Devices





www.hubbell-wiring.com