




ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART, CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS

DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1308

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1960	A	RELEASED	JN	11/18/08	JWM	11/18/08	JWM	11/18/08



Notes:

- Insertion Loss: Ceramic <=0.15dB
- Retentions force: 200~600 Grams.
- Durability: 500MATING./
- Operating Temperature: -40°C ~ 80°C.
- Flammability Grade: UL94V-0
- Sleeve Material: Ceramic (1)
- Body attributes: Plastic, Blue (1)
- Mounting Plate: Stainless Steel (1)
- Dust Cap: Blue (2)

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
Jason Nash	11/18/08
CHECKED BY:	DATE:
JWM	11/18/08
APPROVED BY:	DATE:
JWM	11/18/08

DRAWING TITLE:			
SC Adapter Simplex			
SIZE	DWG. NO.	ELECTRONIC FILE	REV
A	SPC22796	70M9866.DWG	A
SCALE:	NTS	U.Q.M.: Millimeters	SHEET: 1 OF 1