

PART NO.

MC32601

REVISIONS								
ECN#	ECN # REV DESCRIPTION		DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED		26/02/09	Suresh	26/02/09	Farnell	12/03/09

: 1.0A ac/dc.


: 30V ac/dc.


: Nylon 6T.

: -40°C to +105°C.

RoHS

Compliant





Specifications:

Current rating Voltage rating

 $\begin{tabular}{lll} Maximum contact resistance & : 20mΩ. \\ Minimum insulation resistance & : 1000MΩ. \\ \end{tabular}$


Withstanding voltage : 1000M\(\Omega\). : 750V ac for one minute.

Operating temperature range **Material and Finish:**

Insulator
Contact

Contact : Phosphor bronze.
Plating : Gold plated on contact area tin

plated on solder tail.
Shell : Brass, nickel plated.



Dimensions : Millimetres

TOLERANCES:

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
Ramya	26/02/09
CHECKED BY:	DATE:
Suresh	26/02/09
APPROVED BY:	DATE:
Farnell	12/03/09


E:	DRAW	ING TITLE:						
19		U	SB Socket - Type A, R/A, SMT					
E:	SIZE	DWG NO.		ELEC	TRONIC FIL	E	Т	REV
19] A		M10001949	1696541-TDS_DWG				Α
E: 19	SCALE: NTS		U.O.M.: mm		SHEET:	1	OF	2



PART NO.

MC32601

1		REVISIONS							
	ECN#	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
	-	Α	RELEASED	Ramya	26/02/09	Suresh	26/02/09	Farnell	12/03/09



Dimensions : Millimetres

Part Number Table

Description	Part Number			
Socket, USB, PCB, R/A, Type A, SMT	MC32601			

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

the Premier Farnell Group e use of it other than for TOLERANCES:

TOLERANCES.
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.
DIMENSIONS ARE
FOR REFERENCE
PURPOSES ONLY.

DRAWN BY:	DATE:
Ramya	26/02/09
CHECKED BY:	DATE:
Suresh	26/02/09
APPROVED BY:	DATE:
Farnell	12/03/09

:	DRAWI	NG TITLE:							
)			U	JSB Socket - Type A, R/A, SMT					
:	SIZE A	DWG NO.		M10001949		TRONIC FII 541-TDS		RE A	
:	SCALE: NTS		U.O.M.: mm		SHEET:	2 OF	- 2		