




PART NO.

MC32605

	REVISIONS							
ECN#	CN # REV DESCRIPTION		DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED		26/02/09	Suresh	26/02/09	Farnell	12/03/09







Dimensions : Millimetres

Specifications:

 $\begin{tabular}{lll} Current rating & : 1.0A ac/dc. \\ Voltage rating & : 30V ac/dc. \\ Maximum contact resistance & : 20m \Omega. \\ Minimum insulation resistance & : 1000M \Omega. \\ \end{tabular}$

Withstanding voltage : 750V ac for one minute. Operating temperature range : -40°C to $+105^{\circ}\text{C}$.

Materials:

Insulator : High temperature plastic nylon 6T.

Insulator colour : Black.
Contact : Brass.

Plating : Gold plated on contact area tin

plated on solder tails.

RoHS Compliant

Shell : Nickel plating.

Mechanical characteristics:

Insertion force rating : 1.0 to 2.0kg/pc. Withdrawal force rating : 0.8 to 2.0kg/pc.

I ne data sheet and its Contents (the information of policy to the Perimer Farinet Lord).

New York of the Content of the Content of the Content of the Lord of it of the I then for any intellectual property rights be granted. The Information is subject to change without notice and replaces aid data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or emission from I not for any use made of It. Users of this data sheet should check for themselves the information and the suitability of the production of the Content of the Content

TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:				-	
UNI ESS OTHERWISE	Veena 26/02/09 USB Plug - Type A				, Straight, SMT			
SPECIFIED,	CHECKED BY:	DATE:	SIZE DWG NO.				FLECTRONIC FILE	
DIMENSIONS ARE FOR REFERENCE	Suresh	26/02/09	Δ		M10001947		1696546-TDS DWG	
PURPOSES ONLY.	APPROVED BY:	DATE:	⊢		U.O.M.: mm		· · · · · -	-
	Farnell	12/03/09	SCAL	E: NTS			SHEET: 1 OF	2




PART NO.

MC32605

		REVISIONS						
ECN#	CN # REV DESCRIPTION		DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Veena	26/02/09	Suresh	26/02/09	Farnell	12/03/09

PCB Layout



Dimensions : Millimetres

Part Number Table

Description	Part Number				
Plug, USB, Type A, SMT	MC32605				

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

REV

Α

2 OF 2

TOLERANCES:
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
Veena	26/02/09
CHECKED BY:	DATE:
Suresh	26/02/09
APPROVED BY:	DATE:
Farnell	12/03/09

	DRAW	ING TITLE:								
] U			US	SB Plug - Type A, Straight, SMT						
	size A	DWG NO.	N/100010/7			TRONIC FII 546-TDS ₋		/G		
SCALE: NTS		U.O.M.: mm		SHEET:	2	OF				