



PART NO.

2211S-10G

REVISIONS								
ECN #	REV	REV DESCRIPTION		DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Veena	01/8/08	Suresh	01/8/08	G. C	15/8/08







Dimensions : Millimetres

Specifications:

Withstanding voltage : 600V ac for one minute.

Operating temperature range : -40°C to +105°C.

Material and Finish:

Insulator : High temperature plastic (PBT).

Insulator colour : Black.

Contact : Copper alloy.

Plated : Gold plated.

Inside as sheet and its contents (the "information") belong to the Premier Famel Group (the "Corup") or an elemented to It, to locate or granted for the use of I other than for of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Circup assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of It. Users of this data sheet should check for themselves the Information and the suitability of the prod-contribution of the Information of the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) for example due. This will not operate to limit or restrict the Circup's liability for death or personal injury resulting from the negligence.

пр	TOLERANCES:	DRAWN BY:	DATE:	DRAWI	NG IIILE:						- 1
1-	UNLESS OTHERWISE	Veena	01/08/08	ĺ	5	Single Row Right A	ngle	 10 Wa 	y		
IS	SPECIFIED,	CHECKED BY:	DATE:	SIZE	DWG NO.		ELEC	TRONIC FIL		Т	REV
	DIMENSIONS ARE FOR REFERENCE	Suresh	01/08/08	Δ		M10001420	22118	-XXG-F1 7	DW	ď	Α
	PURPOSES ONLY.	APPROVED BY:	DATE:	- ^ -							-
iii. 9.		G.Cook	15/08/08	SCAL	E: NTS	U.O.M.: mm		SHEET:	1	OF	2



PART NO.


2211S-10G

REVISIONS								
ECN#	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Veena	01/8/08	Suresh	01/8/08	G. C	15/8/08

Part Number Table

Description	Part Number
Header, 1 Row, Vertical, 10 Way	2211S-10G

Part Number Explanation:



: G = Gold Plated. Plated

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

chied and its corderés (the "Information") belong to the Premier Famal Group
up or are all learness of it. No licence a granted for the use of it often than for
on purposes in connection with the products to which it retales. No licence
ellectual property rights is granted. The Information is subject to change withand replaces all data sheets previously supplied. The Information supplied in
the accuracy or
and replaces all data sheets previously supplied. The Information autoput
to the accuracy or
and replaces all data sheets previously supplied. The Information and the PECEIFIED,
DIMPOSES OF THE PROPERTY of the Production of the PECEIFIED,
DIMPOSES ONLE
TOURNESS OF THE PROPERTY OF THE PROPE

	TOLERANCES.
	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE
	DIMENSIONS ARE
	FOR REFERENCE
	PURPOSES ONLY.
ı	

DRAWN BY:	DATE:
Veena	01/08/08
CHECKED BY:	DATE:
Suresh	01/08/08
APPROVED BY:	DATE:
G.Cook	15/08/08

Single Row Right Angle - 10 Way									
SIZE A	DWG NO.	M10001420	ELECTRONIC FILE 2211S-XXG-F1_7_DWG	REV A					
SCALE: NTS		U.O.M.: mm	SHEET: 2 OF	2					