




PART NO.

2212S-08SG-85

REVISIONS								
ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Veena	01/8/08	Suresh	01/8/08	G. C	15/8/08







## Specifications:

Current rating : 3.0A ac/dc. Voltage rating : 250V ac/dc. :  $20m\Omega$ . Maximum contact resistance : 1000MΩ. Minimum insulation resistance

Withstanding voltage : 600V ac for one minute. : -40°C to +105°C. Operating temperature range

Material and Finish:

Insulator : High temperature plastic (PBT).

Insulator colour : Black.

Contact : Phosphor Bronze. Finish : Selective gold plated.

Dimensions : Millimetres

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DATE: DRAWN BY: Veena 01/08/08 CHECKED BY: DATE: Suresh 01/08/08 APPROVED BY: DATE: G.Cook 15/08/08

DRAWING TITLE: SIZE DWG NO. Α

SCALE: NTS

U.O.M.: mm

PCB Socket Double Row Straight - 8 Way ELECTRONIC FILE M10001431

2212S-XXSG-85-F1(REV)\_DWG SHEET: 1

REV

Α



PART NO.

2212S-08SG-85

Τ	REVISIONS								
E	CN#	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
	-	Α	A RELEASED		01/8/08	Suresh	01/8/08	G. C	15/8/08

## **Specification Table**

Number of Positions	Α	В	Part Number		
8	20.82	17.78	2212S-08SG-85		

Dimensions : Millimetres

## **Part Number Explanation:**



**Number of Positions** 

: 08 = 8 Positions.

Plated Plastic Height : SG = Selective Gold Plated.

: 85 = 8.5mm.

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

	DRAWN BY:	DATE:
	Veena	01/08/08
	CHECKED BY:	DATE:
	Suresh	01/08/08
	APPROVED BY:	DATE:
	G.Cook	15/08/08

:	DRAW	NG TITLE:						
		P	CB S	ocket Double F	Row Str	aight -	8 Way	<i>'</i>
:	SIZE	DWG NO.			ELEC	REV		
	Α		N	И10001431		G-85-F1(REV		Α
:	SCAL	E: NTC		II O M · mm		енеет.	2 0	