


MB1-130-01-F-S-01-SL



MB1-120-01-L-S-02-SL

1 mm MINI CARD GUIDE MB1 SERIES

Mates with:
 (0,80mm) .031" PCB,
 (1,60mm) .062" PCB

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?MB1

Insulator Material: Black LCP
Contact Material: BeCu
Plating: Sn or Au over 50µ" (1,27µm) Ni
Operating Temp Range: -55°C to +125°C
Insertion Depth: (5,26mm) .207" to (6,10mm) .240"
RoHS Compliant: Yes

Processing:

Max Processing Temp: 230°C for 60 seconds, or 260°C for 20 seconds 3x
Lead-Free Solderable: Yes
SMT Lead Coplanarity: (0,10mm) .004" max (20-30) (0,15mm) .006" max (40-50)

Important Note: Samtec recommends that pads on the mating board be Gold plated.

Note: Other Gold plating options available. Contact Samtec.

Note: Some sizes, styles and options are non-standard, non-returnable.

MB1	1	NO. OF PINS	01	PLATING OPTION	S	CARD SLOT	SL	OTHER OPTION
------------	----------	--------------------	-----------	-----------------------	----------	------------------	-----------	---------------------

20, 30, 40, 50

(No. of Positions + 2) x (1,00) .03937 + (4,06) .160

-F
= Gold flash on contact, Matte Tin on tail

-L
= 10µ" (0,25µm) Gold on contact, Matte Tin on tail

Specify CARD SLOT from chart

CARD SLOT	A	MATES WITH BOARD THICKNESS
-01	(0,97) .038	(0,80) .031
-02	(1,83) .072	(1,60) .062


-N
= No Card Guides

-N OPTION

ALSO AVAILABLE

Flex Card System

- 2mm (.0787") (FCT/EMT Series) and .050" (1,27mm) (FCF/EMF Series) systems
- Vertical and horizontal
- Header with snap-on card guides for design flexibility
- Elevated design now available
- PCMCIA (PCMT/PCMS Series) Compact Flash (CFT/CFS Series) compatible applications available
- Ideal for multiple add-on cards
- Solder locks for mechanical stability
- Any size from 40 to 100 contacts



Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 • Fax: 812-948-5047

SAMTEC SILICON VALLEY • Tel: 408-395-5900 • Fax: 408-395-1520

SAMTEC UK • Tel: 44 01236 739292 • Fax: 44 01236 727113

SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0 • Fax: +49 (0) 89 / 89460-299

SAMTEC FRANCE • Tel: 33 01 60 95 06 60 • Fax: 33 01 60 95 06 61

SAMTEC ITALY • Tel: 39 039 6890337 • Fax: 39 039 6890315

SAMTEC NORDIC/BALTIC • Tel: +46-84477280 • Fax: +46-87420413

SAMTEC ISRAEL • Tel: 972-3-7526600 • Fax: 972-3-7526690

SAMTEC INDIA • Tel: +91-80-3272 1612 • Fax: +91-80-4152 8187

SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 • Fax: 65 6841-1502

SAMTEC JAPAN • Tel: 045-475-1385 • Fax: 045-475-1340

SAMTEC CHINA • Tel: 86-21-61103766 • Fax: 86-21-5423 4575

SAMTEC TAIWAN • Tel: 886-2-2735-6109 • Fax: 886-2-2735-5036

SAMTEC HONG KONG • Tel: 852-2600-4850 • Fax: 852-2600-4842

SAMTEC KOREA • Tel: 82-31-717-5685 • Fax: 82-31-717-5681

SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112 • Fax: 27 86 6714432

SAMTEC ANZ • Tel: 613 9512 7747 • Fax: 613 9512 7745