



RECOMMENDED HOLE LAYOUT

1. ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS.
- △ BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
- △ .000100-.000200 MATTE TIN-LEAD OVER .000050 NICKEL.
- △ .000100-.000200 BRIGHT TIN OVER .000050 NICKEL.
- △ PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
- △ HOUSING MATERIAL: FLAME RETARDANT THERMOPLASTIC; COLOR-BLACK. POSTS: PHOS BRONZE
- △ .000100-.000200 MATTE TIN OVER .000050 NICKEL.

PLATING	C	B	A	NO OF POSN	PART NUMBER
△	3.984	3.900	39	40	9-103323-0
△	3.884	3.800	38	39	8-103328-9
△	3.784	3.700	37	38	8-103328-8
△	3.684	3.600	36	37	8-103328-7
△	3.584	3.500	35	36	8-103328-6
△	3.484	3.400	34	35	8-103328-5
△	3.384	3.300	33	34	8-103328-4
△	3.284	3.200	32	33	8-103328-3
△	3.184	3.100	31	32	8-103328-2
△	3.084	3.000	30	31	8-103328-1
△	2.984	2.900	29	30	8-103328-0
△	2.884	2.800	28	29	7-103323-9
△	2.784	2.700	27	28	7-103323-8
△	2.684	2.600	26	27	7-103323-7
△	2.584	2.500	25	26	7-103323-6
△	2.484	2.400	24	25	7-103323-5
△	2.384	2.300	23	24	7-103323-4
△	2.284	2.200	22	23	7-103323-3
△	2.184	2.100	21	22	7-103323-2
△	2.084	2.000	20	21	7-103323-1
△	1.984	1.900	19	20	7-103323-0
△	1.884	1.800	18	19	6-103323-9
△	1.784	1.700	17	18	6-103323-8
△	1.684	1.600	16	17	6-103323-7
△	1.584	1.500	15	16	6-103323-6
△	1.484	1.400	14	15	6-103323-5
△	1.384	1.300	13	14	6-103323-4
△	1.284	1.200	12	13	6-103323-3
△	1.184	1.100	11	12	6-103323-2
△	1.084	1.000	10	11	6-103323-1
△	.984	.900	9	10	6-103323-0
△	.884	.800	8	9	5-103323-9
△	.784	.700	7	8	5-103323-8
△	.684	.600	6	7	5-103323-7
△	.584	.500	5	6	5-103323-6
△	.484	.400	4	5	5-103323-5
△	.384	.300	3	4	5-103323-4
△	.284	.200	2	3	5-103323-3
△	.184	.100	1	2	5-103323-2
△	.084	---	1	5-103323-1	

PLATING	C	B	A	NO OF POSN	PART NUMBER
△	1.184	1.100	1	2	4-103323-2
△	3.984	3.900	39	40	4-103323-1
△	3.884	3.800	38	39	4-103323-0
△	3.784	3.700	37	38	3-103323-9
△	3.684	3.600	36	37	3-103323-8
△	3.584	3.500	35	36	3-103323-7
△	3.484	3.400	34	35	3-103323-6
△	3.384	3.300	33	34	3-103323-5
△	3.284	3.200	32	33	3-103323-4
△	3.184	3.100	31	32	3-103323-3
△	3.084	3.000	30	31	3-103323-2
△	2.984	2.900	29	30	3-103323-1
△	2.884	2.800	28	29	2-103323-9
△	2.784	2.700	27	28	2-103323-8
△	2.684	2.600	26	27	2-103323-7
△	2.584	2.500	25	26	2-103323-6
△	2.484	2.400	24	25	2-103323-5
△	2.384	2.300	23	24	2-103323-4
△	2.284	2.200	22	23	2-103323-3
△	2.184	2.100	21	22	2-103323-2
△	2.084	2.000	20	21	2-103323-1
△	1.984	1.900	19	20	2-103323-0
△	1.884	1.800	18	19	1-103323-9
△	1.784	1.700	17	18	1-103323-8
△	1.684	1.600	16	17	1-103323-7
△	1.584	1.500	15	16	1-103323-6
△	1.484	1.400	14	15	1-103323-5
△	1.384	1.300	13	14	1-103323-4
△	1.284	1.200	12	13	1-103323-3
△	1.184	1.100	11	12	1-103323-2
△	1.084	1.000	10	11	1-103323-1
△	.984	.900	9	10	1-103323-0
△	.884	.800	8	9	103323-9
△	.784	.700	7	8	103323-8
△	.684	.600	6	7	103323-7
△	.584	.500	5	6	103323-6
△	.484	.400	4	5	103323-5
△	.384	.300	3	4	103323-4
△	.284	.200	2	3	103323-3
△	.184	.100	1	2	103323-2
△	.084	---	1	1	103323-1

THIS DRAWING IS A CONTROLLED DOCUMENT. (REV) DATE BY
 JOHN KNITTLE (REV) DATE BY
 ELCONDIS CORPORATION
 1000 W. MARKET STREET
 HARRISBURG, PA 17105-2808

Elcondis
 Tye Electronics Corporation
 Harrisburg, Pa 17105-2808

DESCRIPTION: HEADER ASSY, MOD II, BREAKAWAY, SINGLE ROW, 100, RIGHT ANGLE, WITH .025 SQUARE POSTS

MATERIAL: SEE TABLE

CUSTOMER DRAWING: A1 00779 (REV) 103323

DATE: 8-1

REV: 1 OF 1

BY: K