



RECOMMENDED HOLE LAYOUT

- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS.
- BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
- .000100-.000200 MATTE TIN-LEAD OVER .000050 NICKEL.
- .000100-.000200 MATTE TIN OVER .000050 NICKEL.
- HIGH TEMPERATURE CONFIGURATION

REMARKS	PLATING	C	B	A	NO OF POSN	PART NUMBER
△	△	3.984	3.900	39	80	9-103324-0
△	△	3.884	3.800	38	78	8-103324-9
△	△	3.784	3.700	37	76	8-103324-8
△	△	3.684	3.600	36	74	8-103324-7
△	△	3.584	3.500	35	72	8-103324-6
△	△	3.484	3.400	34	70	8-103324-5
△	△	3.384	3.300	33	68	8-103324-4
△	△	3.284	3.200	32	66	8-103324-3
△	△	3.184	3.100	31	64	8-103324-2
△	△	3.084	3.000	30	62	8-103324-1
△	△	2.984	2.900	29	60	8-103324-0
△	△	2.884	2.800	28	58	7-103324-9
△	△	2.784	2.700	27	56	7-103324-8
△	△	2.684	2.600	26	54	7-103324-7
△	△	2.584	2.500	25	52	7-103324-6
△	△	2.484	2.400	24	50	7-103324-5
△	△	2.384	2.300	23	48	7-103324-4
△	△	2.284	2.200	22	46	7-103324-3
△	△	2.184	2.100	21	44	7-103324-2
△	△	2.084	2.000	20	42	7-103324-1
△	△	1.984	1.900	19	40	7-103324-0
△	△	1.884	1.800	18	38	6-103324-9
△	△	1.784	1.700	17	36	6-103324-8
△	△	1.684	1.600	16	34	6-103324-7
△	△	1.584	1.500	15	32	6-103324-6
△	△	1.484	1.400	14	30	6-103324-5
△	△	1.384	1.300	13	28	6-103324-4
△	△	1.284	1.200	12	26	6-103324-3
△	△	1.184	1.100	11	24	6-103324-2
△	△	1.084	1.000	10	22	6-103324-1
△	△	.984	.900	9	20	6-103324-0
△	△	.884	.800	8	18	5-103324-9
△	△	.784	.700	7	16	5-103324-8
△	△	.684	.600	6	14	5-103324-7
△	△	.584	.500	5	12	5-103324-6
△	△	.484	.400	4	10	5-103324-5
△	△	.384	.300	3	8	5-103324-4
△	△	.284	.200	2	6	5-103324-3
△	△	.184	.100	1	4	5-103324-2
△	△	.084	---	2	5	103324-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

MAZETELLI 190701
 JOHN KENTLE
 JOHN KENTLE
 JOHN KENTLE
 JOHN KENTLE

ASSEMBLY, HEADER, BREAKAWAY, MOD II,
 DOUBLE ROW, 100 X 100 D/A, RIGHT ANGLE,
 WITH .025 SQUARE POSTS

SEE TABLE

CUSTOMER DRAWING

DATE 4.1