

22A-972

LOW VOLTAGE CONNECTORS

REF	ITEM	DESCRIPTION AND PART NO.
DC-8		DC Connector Pin/Ring Type. (Rated 12V-1A) Miniature Version For PC Mounting. DC8 - 1.3mm. Ø Pin. . . . . (FC68145) Compatible with plug DCPP3.
DC-9 DC-9A		DC Connector Pin/Ring Type. (Rated 12V-5A) Designed to fit into a moulded cavity or may be PC mounted. With integral switch. DC9 - with 2.1mm. Ø pin. . . . (FC68146) DC9A - with 2.5mm. Ø pin . . . (FC681461)
DC10A DC-10B SCD-026		DC Connector Pin/Ring Type. (Rated 12V-5A) May be PC mounted or hard wired. With switch. DC10A - with 2.1mm. Ø pin . . (FC68148) DC10B - with 2.5mm. Ø pin . . (FC68149) SCD-026/026A. Chassis Mount model. Refer to office.
DC-12A DC-13A		DC Connector Pin/Ring Type. Switched. DC12A - with 2.1mm. Ø pin. PC type. (FC681485) DC12B - with 2.5mm. Ø pin. . . . (FC681486) DC13 Designed for chassis mounting. DC13A - with 2.1mm. Ø pin . . . . (FC681492) DC13B - with 2.5mm. Ø pin . . . . (FC681493)
DC468 DC1463		Combined AC/DC Inlet - PC Type. DC468 - Switch operates when either AC or DC plug is inserted. AC socket is non polarized. DC socket with 2.5mm. Ø pin. . . . (FC68430) DC1463 - As DC468 but w/o DC inlet (FC68431) REFER TO SALES FOR MATCHING AC/DC CORDS.
DCPP1 DCPP2 DCPP3		DC Connectors (Rated 12V-5A). Colour Black. DCPP1 - DC plug 2.1mm. Ø hole (FC68147) DCPP2 - DC Plug 2.5mm. Ø hole. (FC681471) DCPP3 - DC Plug 1.3mm. Ø hole. (FA67555) NOTE. Careful soldering is required due to small size.
FC6815 DC LEADS		DC 'Spider' Multi-Connector. Four types of 2 pole plug moulded onto 2 mts. of cable. Colour Black. . . . . (FC6815) NOTE. Moulded DC leads are made to order for OEM.
CCB-1 CCB-1A		PP3 Battery Connector. Professional Quality. Tough moulded body with cable strain relief. UL - FR Cable. Wires Red/Black. CCB-1 - Cable length 220mm. . . . (FC6830) CCB1-A - 'T' Type. cable length 220mm. . . . . (FC6831)
CCB-2		PP3 Battery Connector. 'T' Type. Commercial quality with soft vinyl body internal fibre core and cable strain relief. UL - FR cable. Wires 220mm. long. Red/Black. . . (FC68365)
C16 C17		2 Pole Moulded Polarized Line Cord. Rated 250VAC.-1A. Colour Black. 2x0.75mm. HAR cable. 1 mtr. long. C16 - Male version. . . . . (OD655275) C17 - Female version. . . . . (OD655276) C16/C17 - Male to Female version. (OD655274)
C14		Chassis Mounting Socket. Rated 250VAC.-1A. Mates with C17. Colour Black. Two Screw or pop rivet fixing. . . . (OD655277)