



Twinaxial

## TWINAXIAL PLUGS, RECEPTACLES

Cable/ Description		Cable Attachment		Dimensions, inches (millimeters)				Notes			Mtg. Hole	IBM Ref. Number	Amphenol Number	Fig.
		Outer	Inner	a	b	c	e	CAI	Plt.	Ins.				
<b>RG-22</b>	Plug	Clamp	Solder	1.75(44.5)	.875(22.2)	.444(11.3)●	—	C19	P4	D6	—	5052750	<b>32225</b>	1
	Receptacle, Front Mount, Solder Cup Terminals			1.58(40.1)	.945(24.0)	.787(20.0)	.295(7.5)	—	P7	D25	Y	—	<b>82-5590-RFX</b>	2
	Receptacle, Front Mount, Solder Cup Terminals			1.58(40.1)	.945(24.0)	.787(20.0)	.295(7.5)	—	P1	D25	Y	—	<b>82-5590-2RFX</b>	2
	Panel Receptacle	—		1.19(30.2)	1.00(25.4)	—	—	—	P4	D6	T	—	<b>6225</b>	3
<b>Times AA-6026, AA6076, AA-6079</b> <b>Brand Rex T8756A</b> <b>Belden 8227, 9207</b> <b>IBM 7362211</b>	Plug	Clamp	Solder or Crimp	1.89(48.0)	.890(22.6)	.340(8.7)●	—	C19	P1	D12	—	7362229	<b>82-5589</b>	4
1.89(48.0)				.890(22.6)	.340(8.7)●	—	C19	P15	D22	—	—	<b>82-5589-RFX</b>	4	
1.85(47)				.890(22.6)	.340(8.7)●	—	C10	P27	D19	—	—	<b>82-GB635-CR</b>	5	

● accommodates cable diameter