

RED INDICATES ORIGINAL

DASH NO		FIG	CABLES ACCOMMODATED	A DIM	B FLATS	C HEX	ASSEMBLE PER
-1/A			RG-58				
-1/U			ESSEX 621-7115				
-2/A			RG-59				
-12/A			BELDEN 8279				
-2/A			AT&T 730A				
-12/B							
-3		1.3	RG-223	.960	.437	.437	TAI-101
-12/C							
-3A			RG-55				
-12/D							
-4			RG-122				
-14			BELDEN 8218				
-5/A			RG-174				
-15/A			RG-187				
-9A			RG-196				
-5B			HEWLETT-PACKARD 8120-1107				
-12/E		1	BELDEN 9231	1.001	.500	.500	TAI-119
-6							
-12/F							
-12/G							
-21			RG-303				
-12/H							
-22			RG-180				
-12/I							
-31			BRIMMAN 628756P1				
-12/J			RG-187 DEL SH D				
-34			BELDEN 8228	.960	.437	.437	TAI-101
-12/K							
-36			275-9981 MICRODOT				
-12/L			B16-569 AMPLEX				
-37			810 RAYCHEM				
-12/M							
-41			RG-304				
-12/N			8248 BELDEN				
-44			BRAND-REX 8749				
-12/O			SCRE C06C032				
-51							
-12/P		1	88281 BELDEN	1.001	.500	.500	TAI-119
-52			89120 BELDEN				
-12/Q							
-53			89555 BELDEN				
-12/R		1.3	734A.AT&T	.960	.437	.437	TAI-101
-63							
-12/S							
-85			RG-405				
-12/T		2	RG-402				TAI-130
-141							

FIG 1 ▲

- 1 SHOWN

FIG 2 ▲

- .086 SHOWN

FIG 3 ▲▲

- 1 SHOWN

INCH	MM
.005	0.13
.030	0.76
.095	2.44
.125	3.18
.250	6.35
.312	7.92
.350	8.89
.437	11.10
.500	12.70
.624	15.85
.850	21.59
1.001	25.43
1.846	46.88

▲ IF SAFETY WIRE & BEND RELIEF SPRINGS REQUIRED ADD SUFFIX "SR" TO MODEL NO. (NOT AVAILABLE WITH CABLE GROUPS -6, -U6, -9E, -U6E, -S1, -U51, -52, -U52, -63, -U63, -086, -U086, -141 & -U141)

▲ IF BEND RELIEF SPRINGS REQUIRED ADD SUFFIX "BR" TO MODEL NO. (SEE FIG 3) (NOT AVAILABLE WITH CABLE GROUPS -6, -U6, -9E, -U6E, -S1, -U51, -52, -U52, -63 & -U63)

▲ IF SAFETY WIRE REQUIRED ADD SUFFIX "S" TO MODEL NO (PL40S/UPL40S)

4. DASH NO DENOTES CABLE GROUP EXCEPT "U" PREFIX DENOTES 75 OHM VERSION

3. MALE TYPE TNC COAXIAL CABLE PLUS BOTH 50 & 75 OHM VERSIONS

2. FINISH: TF8-1A (NICKEL)

1. ALL DIM ARE IN INCHES

▲ FOR CABLE GROUPS -1 & -U1 SUPPLY 1 EA ACA1
FOR CABLE GROUPS -2 & -U2 SUPPLY 1 EA ACA2
FOR CABLE GROUPS -5 & -U5 SUPPLY 1 EA ACA5
MAY BE ASSEMBLED TO CABLE/CONNECTOR ASSY USING 3M SCOTCHBRIP NO. 1099 PLASTIC ADHESIVE, OR EQUIV.)

▲ IF PLASTIC STRAIN RELIEF REQUIRED, ADD SUFFIX "BY" TO MODEL NO. (ONLY AVAILABLE WITH -1, -U1, -2, -U2, -5, -U5)

QTY	DESCRIPTION	PART NUMBER	ITEM
10, UNLESS SPECIFIED			
BY XXX 2 .005			
XXXX			
ANL40S			
11-02	1-0214	105-0489	DWN 1 3 6 13/18/60
12-06	1-0205	105-0241	CHK UJA 3/23/60
105-0717	1-0205	205-0001	ENGR WZ 3/23/60
105-0623	1-0203	NEXT ASSY	APPR 2 3-23-60

REV	ED	DESCRIPTION	1-0014	SH 1
AF	18913	ADDED NOTE 3 & REDRAN	DWN APPROVED DATE	3 8 UJA/af/60