

RED INDICATES ORIGINAL

DASH NO		FIG	CABLES ACCOMMODATED	ASSEMBLE PER
-1			RG-58	
-U1			ESSEX 621-715	
-2			RG-59	
-U2				
-2A			BELDEN 8279	
-2B			W. E. CO. 730A	
-U2B				
-3			RG-223	
-U3				
-3A			RG-55	
-U3A				
-4			RG-122	
-U4			BELDEN 8218	
-5			RG-174	
-U5			RG-187	
-5A			RG-196	
-U5A				
-5B			HEWLETT-PACKARD	
-U5B			8120-1107	
-21				
-U21			RG-303	
-22			RG-180	
-U22				
-31			GRUMMAN 6C8756P1	
-U31			RG-187, DBL. SHLD.	
-34			BELDEN 8228	
-U34				
-36			275-3991 MICRODOT	
-U36			615-568 AMPLEX	
-37			810 RAYCHEM	
-U37				
-41			RG-304	
-U41			8248 BELDEN	
-44			GRAND-REX 8748	
-U44			BORE COB6032	
-53			69555 BELDEN	
-U53				
-63			734A. AT&T	
-U63				
-085			RG-405	
-U085				
-141			RG-402	
-U141				

FIG 1 - 1 SHOWN

TNCH	MM
.005	0.13
.030	0.76
.098	2.44
.125	3.18
.187	4.75
.250	6.35
.281	7.14
.284	7.21
.312	7.92
.437	11.10
.630	16.00
.635	16.13
.750	19.05
.750	20.07
.830	21.08
1.000	25.40
1.406	35.71
1.846	46.89

FIG 2 - 085 SHOWN

FIG 3 - 1 SHOWN

RECOMMENDED PANEL CUTOUT

SCALE: NONE

IF BEND RELIEF SPRING REQUIRED (FIG 3)
ADD SUFFIX "BR" TO MODEL NO (NOT AVAILABLE WITH CABLE GROUPS -53, -U53, -085, -U085, -141 & -U141)

- MAX PANEL THK .187
- DASH NO DENOTES CABLE GROUP EXCEPT "U" PREFIX DENOTES 75 OHM VERSION
- FINISH: TP8-1A (NICKEL)
- ALL DIM ARE IN INCHES

QTY	DESCRIPTION	PART NUMBER	ITEM
110-0002	TOL UNLESS SPECIFIED		
105-0717	.XX ± .005		
105-0623	ANGLE		
305-0361	DWN DKL 7-1-81		
155-0393	CHK S.M. 7-13-81		
102-1016	ENGR		
NEXT ASSY	APPR		

TROMPETER ELECTRONICS, INC.		8026/UBJ26	
MATERIAL	CODE IDENT	DRAWING NO.	REV
	14949	1-0341	T
SCALE 2:1		DATE 10/13/89	SHEET 1 OF 2

REV	ED	DESCRIPTION	DWN I	APPROVED	DATE
1	8367	.830 DIA MAX WAS .810 DIA	DKC		7-23-77

STK # 55
SWS SIZE C

DATA CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO TROMPETER ELECTRONICS, INC. AND SHALL NOT BE REPRODUCED, COPIED, OR USED FOR REPRODUCTION WITHOUT EXPRESS WRITTEN PERMISSION.

REVISIONS **1-0341** SH 1
DWN I APPROVED DATE