


GSD

UG-536B/U



NOTES:

1. FOR USE WITH RG-55, 58, 141, 142, AND 400/U CABLE GROUPS.
2. FOR CABLING INSTRUCTIONS SEE CP-1014.
3. INTERFACE PER MIL-STD-348, FIG. 304-1.
4. MATERIALS:
 - INSULATOR-TEFLON, ASTM-D-1457
 - GASKET-SILICONE RUBBER, ZZ-R-765
 - C-RING } PHOSPHOR BRONZE, QQ-B-750
 - OUTER CONTACT }
 - ALL OTHER METAL PARTS-BRASS, ASTM-B16
5. FINISHES:
 - ALL METAL PARTS-SILVER PLATE PER QQ-S-365
6. ELECTRICAL CHARACTERISTICS:
 - NOMINAL IMPEDANCE-50 OHMS
 - FREQUENCY RANGE-DC TO 11 GHZ
 - WORKING VOLTAGE-1000 VRMS

REVISIONS	
ISSUE	CHANGES
7	CN 26555 D EAJ 08/11/84

KAM1773

SCALE	4:1
APPROX SURFACE AREA	
KN-57-05	
USED ON	
REF:	RE-B-49090A
PLUG, N	
DRAWN KH	DATE 02/13/92
DESIGN MJB	DATE 02/14/92
APPR.	DATE

GSD

KINGS
ELECTRONICS CO., INC.
TUCKAHOE, NEW YORK 10707

UG-536B/U