

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 16\_MMCX-50-2-1/111\_O

Rev.: B



### Description

Right angle cable plug for semi-rigid cable

Interface standards  
SUHNER-MMCX



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 6 GHz

#### Mechanical Data

Centre contact soldered  
Outer contact soldered  
Weight 0.0006 kg

#### Environmental Data

Operating Temperature -55 °C to 155 °C

#### Material Data

##### Piece Parts

Centre contact  
Outer contact  
Body  
Insulator

##### Material

Bronze  
Brass  
Brass  
PFA / PTFE

##### Surface Plating

Gold Plating (Nickel underplated)  
Gold Plating  
Gold Plating

### Related Documents

Catalogue drawing DOU-00006007  
Assembly instruction DOC-0000180777

### Ordering Information

Single package 16\_MMCX-50-2-1/111\_OE  
Bulk 100 pcs package 16\_MMCX-50-2-1/111\_OH

### Additional Information

Suitable cable EZ\_86\_TP\_M17

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**

Document: DOC-0000180778 J.00

Issued: 14.07.04

Uncontrolled Copy

Page 1/1