



SUHNER® COAXIAL CONNECTOR DATA SHEET

TYPE 24 SMA-50-2-15 / 111 NH

Description

Straight panel bulkhead cable jack, flange mount

**Rear mount chassis connector
With panel seal**



General Information

SMA Interface dims acc. to: IEC 60169-15_MIL-STD-348A/310_CECC 22110
Weight: 0.0036 Kg / 0.1270 oz

Cable Cable type (recommended): EZ 86-TP/M17

Cable Entry Outer contact: soldered
Centre contact: soldered

Electrical Data Impedance: 50Ω
Frequency range for standard interface: DC ... 18 GHz

Piece Parts

Centre contact:
Outer contact:
Body:
Insulator:

Material

Copper-Beryllium
Copper-Beryllium
Copper-Beryllium
PTFE/PFA

Surface Plating

Gold / nickel underplated
Gold / nickel underplated
Gold / nickel underplated

Fastening nut: Brass Gold / nickel underplated
Gasket: Silicone rubber
Washer: Spring bronze Gold / nickel underplated

Packaging

Bulk 100 pcs

Attachments

Catalogue drawing: 20446_1
Assembly instruction: M09057

Notes

Mounting hole: ML35

Order as 24 SMA-50-2-15 / 111 NH under article number 22645490

WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.



HUBER+SUHNER AG

Interconnect Division

CH-9100 Herisau

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

<http://www.hubersuhner.com>

Issued: 5.12.2001 17:28

Document: TEMP_PDB_2264549
0.PDF

RF_Pa_Ca_C_P
DF

uncontrolled copy

Page 1