

31/01/08

15/02/08

DATE:

SCALE: NTS

Suresh

G.Cook

APPROVED BY:

M10000687

U.O.M.: mm (Inches)

46-01V-1-TGG_DWG

SHEET:

1

Α



PART NO.

46-01V-1-TGG

	REVISIONS								
ECN	N #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-		Α	RELEASED	Sumana	31/1/08	Suresh	31/1/08	G. C	15/2/08

Specifications:

Electrical:

Frequency Range : DC-4GHz. : 50Ohms. Nominal Impedance Maximum Working Voltage : 250V. : 500V. Proof Voltage Maximum VSWR : 1.3.

Materials:

: Brass per JIS-C3604. Bodies

Beryllium Copper per ASTM B196 UNS C17300. Centre Contact : Beryllium Copper per ASTM B196 UNS C17300. : PTFE per ASTM D1457 and ASTM D1710. Insulation

Mechanical:

Interface in accordance with MIL-STD-348A. For use with RG405 or similar style cable.

Cable attachment : Outer: Solder, Inner: Solder

Environmental:

Operating Temperature Range : -65°C to +165°C

Specification Table

Number	Description	Material	Finish	Part Number		
1	Shell	Brass	Gold 3µ" Minimum			
2	Body Beryllium		Goid 5μ Willillindin	46-01V-1-TGG		
3	Insulation	PTFE None ct Beryllium Copper Gold 30µ" Minimum				
4	Centre Contact					
5	Solder Nut	Brass	Gold 3µ" Minimum			

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

REV

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:	DRAWING TITLE:		
Sumana	31/01/08			
CHECKED BY:	DATE:	SIZE	DWG NO	
Suresh	31/01/08	Α		
APPROVED BY:	DATE:	- ^ `		
G.Cook	15/02/08	SCAL	E: NTS	

Striaght Plug - SSMB									
SIZE A	DWG NO.	ı	M10000687		ELECTRONIC FILE 46-01V-1-TGG_DWG				
SCALE: NTS			U.O.M.: mm (Inches)		SHEET:	2	OF	2	