



NOTES:
1. FOR USE WITH RG-8,9,213 & 214 CABLE GROUPS.

UNLESS OTHERWISE SPECIFIED:

1. TOLERANCES: FRACTIONS & 2 PLACE DECIMALS ± .010
3 PLACE DECIMALS ± .004
T. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED THE SUM OF THEIR TOLERANCES.
2. REMOVE ALL BURRS, BREAK SHARP EDGES .005 MAX.
3. NO FILLETS PERMITTED.
4. SURFACE ROUGHNESS 63 MICROINCHES RMS MAX.
5. ALL DIMENSIONS PRIOR TO PLATING.

M39012/02-0003

S-D

REVISIONS	
ISSUE	CHANGES
5	CN 23169 E JEP 13 APR 82
6	CN 32243 A LNM 1 JUN 90

S-D

KN-39-68
REF: SUPERSEDES
US-1186A/U

FINISH _____
SPEC. _____
MATERIAL _____
SPEC. _____

N JACK

DRAWN WLA DATE 8 APR 70
APPR. DAM DATE 28 AUG 70

KINGS ELECTRONICS
40 HARBORLEDALE ROAD
TUCKAHOE, N. Y. 10707

DRAWING NO. M39012/02-0003

ITEM	REQ'D	DESCRIPTION	DRAWING NO.