



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. PHOSPHOR BRONZE PER QQ-B-750
 5. COLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE

1. MAX. PANEL THICKNESS=5.5mm

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	3/1	ISSUE	A	FILE NO.	
7	HEX NUT	NOTE 1	NOTE 3	1	HN16-1/2-28X28	DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4					
6	LOCK WASHER	NOTE 2	NOTE 3	1	LW-16/13X05						
5	LOCK RING	NOTE 2	NOTE 3	1	LR-79/62X08						
4	CONTACT PIN	NOTE 4	NOTE 5	1	B7900-4						
3	INSULATOR	DELTRIN	NATURAL	2	B7996ZZ-3-50						
2	INSULATOR	DELTRIN	WHITE	1	B7771B3-1P						
1	BODY	NOTE 1	NOTE 3	1							

PART NO.	B7771B3-ND3G-50
APPROVED	DATE 10-11-01'
CHECKED	DATE 10-11-01'
DRAWN	DATE 10-11-01'

Amphenol

TITLE BNC FEMALE TO FEMALE BULKHEAD ISOLATED ADAPTOR

DRAWING NO. KJ-B7771B3-ND3G-50

ITEM NO.