

Fuse holder terminal blocks for fuses 5x20 mm .197x.787 in. and 5x25 mm .197x.984 in.

Screw clamp  DIN 1 - DIN3

M 4/8.SF- 4 mm² blocks - 8 mm .315" spacing

Characteristics

Wire size mm ² / AWG	Solid Stranded	IEC	UL	CSA
		NFC DIN	22-12 AWG	22-12 AWG
Voltage		V	630 (1)(2)	600 (1) 250
Current		A	6.3	10 10
Rated wire size		mm ² / AWG	4 mm ² 12 AWG	12 AWG
Wire stripping length		mm / inches	9.5 mm / .37"	
Recommended torque		Nm / lb.in	0.5-0.8 Nm / 4.4-7.1 lb.in	

(1) Insulation voltage of terminal block - operating voltage : according to fuse.
(2) 400 V for block M 4/6.SFT

Selection

Description	Type	Order P/N	Packaging Weight kg
Standard block grey <input type="checkbox"/>	M 4/8.SF	1SNA 115 657 R2500	50
Block with test socket Ø2 mm grey <input type="checkbox"/>	M 4/8.SF	1SNA 115 662 R2200	50
Standard block orange <input type="checkbox"/>	M 4/8.SF2	1SNA 105 135 R1100	50
Standard block beige V0 <input type="checkbox"/>	M 4/8.SF.V0	1SNA 195 657 R2600	50

M 4/8.SFL - 4 mm² blocks - 8 mm .315" spacing

Characteristics

Wire size mm ² / AWG	Solid Stranded	IEC	UL	CSA
		NFC DIN	22-12 AWG	22-12 AWG
Voltage		V	400	600 250
Current		A	6.3	10 10
Rated wire size		mm ² / AWG	4 mm ² 12 AWG	12 AWG
Wire stripping length		mm / inches	9.5 mm / .374"	
Recommended torque		Nm / lb.in	0.5-0.8 Nm / 4.4-7.7 lb.in	

Selection

Description	Type	Order P/N	Packaging Weight kg
Block with fusion indicator neon grey <input type="checkbox"/>	M 4/8.SFL	1SNA 115 661 R2100	50
Block with fusion indicator 24V grey <input type="checkbox"/>	M 4/8.SFD	1SNA 115 663 R2300	50

M 4/8.SN - 4 mm² blocks - 8 mm .315" spacing

Characteristics

Wire size mm ² / AWG	Solid Stranded	IEC	UL	CSA
		NFC DIN	22-12 AWG	24-12 AWG
Voltage		V	630 (1)	600 250
Current		A	6.3	10 10
Rated wire size		mm ² / AWG	4 mm ² 12 AWG	12 AWG
Wire stripping length		mm / inches	9.5 mm / .37"	
Recommended torque		Nm / lb.in	0.5-0.8 Nm / 4.4-7.1 lb.in	

(1) Insulation voltage of terminal block - operating voltage : according to fuse.

Selection

Description	Type	Order P/N	Packaging Weight kg
Standard block grey body/blue grip <input type="checkbox"/>	M 4/8.SN	1SNA 115 659 R0700	50
Standard block beige body/blue V0 grip <input type="checkbox"/>	M 4/8.SN.V0	1SNA 195 659 R0000	50

Accessories

Description	Type	Order P/N	Packaging Weight kg	
End stop	BAM 9.1 mm	1SNA 103 002 R2600	50	
End section	grey <input type="checkbox"/>	FEM8S 1.5 mm	1SNA 116 951 R1500	20
	orange <input type="checkbox"/>	FEM8S 1.5 mm	1SNA 103 923 R1500	20

