








PA44wp

Pillar Terminal Block with Wire Protector (12 poles)



TECHNICAL DATA

		IEC Standards	American Standards
Ratings		750V - 32A	300V - 25A
Wire size		4.0 sqmm	14 ÷ 10AWG
Working Temperature		- 5 ÷ 110°C (short time 140°C)	23 ÷ 221°F
Plastic Material		Polyamide PA6.6 natural colour, UL94 V2, GWT 960°C	
Metal Parts		Cage insert made in nickel plated brass; M3.5 Captive screw made in zinc plated steel; Wire protector made in stainless steel	
Accessories		PA296 - PA228 - PA52 - PA197	
Approvals	File Nr.	Ratings (sqmm/AWG – V – A – T)	Standard References
	CA02.00596	4.0 sqmm - 750V - 32A - 110°C	EN 60998-1; EN 60998-2-1
	CA02.00596	4.0 sqmm - 750V - 32A - 110°C	EN 60998-1; EN 60998-2-1
	121128	4.0sqmm - 450V - 32A - 110°C	DIN EN 60998-1; DIN EN 60998-1/A1; DIN EN 60998-2-1 (VDE 0613)
	E76048 vol. 1 sec. 1	14 ÷ 10 AWG - 300V - 25A - 105 °C	UL 1059; CSA C22-2 N.158-1987
	LR 40455	18 ÷ 10 AWG - 300V - 25A	CSA C22-2 N.158-1987; E.C.N 584B

PACKAGING

Type	P-N	Pack.	Dim. Pack. (LxHxP)	Weight (Kg)
PA 44 WP/12P	102212	200	30x20x40	11.0

DIMENSIONAL DRAWING

