

MA 2,5/5.SNBTA				M 4/6.SNBT...				M 4/6.SNB							
Spacing 5 mm (.200")				Spacing 6 mm + 0,05 (.238")				Spacing 6 mm + 0,05 (.238")							
5 mm block - Switch connection by short blade - Equipped with two test sockets DIA. 2,3 mm / .090"				6 mm block - Switch connection by short blade - Equipped with two test sockets DIA. 2 mm / .079"				6 mm block - Switch connection by long blade							
Color	Type	Part numbers		Color	Type	Part numbers		Color	Type	Part numbers					
Grey / Grey	MA 2,5/5.SNBTA	0115 505.16		Grey / Grey	M 4/6.SNBT1	0115 438.12		Grey / Grey	M 4/6.SNB	0115 686.13					
				Grey / Beige V0	M 4/6.SNBT2	0115 441.15		Orange/Orange	M 4/6.SNB	0105 053.22					
								Beige V0/Beige	M 4/6.SNB.V0	0195 686.14					
Characteristics				Characteristics				Characteristics							
Wire size				Wire size				Wire size							
		IEC	UL	CSA			IEC	UL	CSA			IEC	UL	CSA	
		NFC	DIN				NFC	DIN				NFC	DIN		
Compression clamp	Solid wire	0,5-4 mm ²	24-12 AWG	24-12 AWG	Compression clamp	Solid wire	0,5-4 mm ²	22-10 AWG		Compression clamp	Solid wire	0,5-4 mm ²	22-10 AWG	20-12 AWG	
	Stranded wire	0,5-4 mm ²	24-12 AWG	24-12 AWG		Stranded wire	0,5-4 mm ²	22-10 AWG			Stranded wire	0,5-2,5 mm ²	22-10 AWG	20-12 AWG	
Voltage				Voltage				Voltage							
Rated		320 V	600 V	150 V	Rated		320 V	300 V		Rated		400 V	300 V	300 V	
Pulse		4 kV			Pulse		4 kV			Pulse		4 kV			
Pollution degree		3			Pollution degree		3			Pollution degree		3			
Current				Current				Current							
Rated		10 A	15 A	10 A	Rated		10 A	10 A		Rated		10 A	10 A	10 A	
Wire size				Wire size				Wire size							
Rated / Gauge		4 mm ² / A3	12 AWG	12 AWG	Rated / Gauge		4 mm ² / A4	10 AWG		Rated / Gauge		2,5 mm ² / A4	10 AWG	12 AWG	
Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection	Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection	Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection	Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection
10 mm .39"	3,5 mm .16"	0,4-0,6 Nm 3,5-5,3 lb.in	IP 20 NEMA 1	9,5 mm .374"	4 mm .157"	0,5-0,6 Nm 4,4-5,3 lb.in	IP 20 NEMA 1	9,5 mm .37"	4 mm .16"	0,5-0,6 Nm 4,4-5,3 lb.in	IP 20 NEMA 1	9,5 mm .37"	4 mm .16"	0,5-0,6 Nm 4,4-5,3 lb.in	IP 20 NEMA 1
Type	Part numbers			Type	Part numbers			Type	Part numbers						
FEM6	th. 2,8 mm	0118 368.16		FEM62	th. 3 mm	0114 994.07		FEM62	th. 3 mm	0114 994.07					
SCF6	th. 3,0 mm	0118 707.03						SCF62	th. 3 mm	0103 612.25					
SCF6 V0	V0 th. 3,0 mm	0198 707.04						FEM62 V0	th. 3 mm	0194 994.00					
SCFM6	th. 3,0 mm	0114 825.05		SCFM6	th. 3 mm	0114 825.05		SCFM6	th. 3 mm	0114 825.05					
SCFEX1 (1)	th. 2,4 mm	0103 619.04		SCFEX1 (1)	th. 2,4 mm	0103 619.04		SCFEX1 (1)	th. 2,4 mm	0103 619.04					
SCFEX3 (1)	th. 2,4 mm	0103 620.01		SCFEX3 (1)	th. 2,4 mm	0103 620.01		SCFEX3 (1)	th. 2,4 mm	0103 620.01					
				FC2	DIA. 2 mm	0007 865.26		FC2	DIA. 2 mm	0007 865.26					
CBM5	th. 0,5 mm	0178 745.14		CBM5	th. 0,5 mm	0178 745.14		CBM5	th. 0,5 mm	0178 745.14					
CBM8	th. 0,8 mm	0178 746.15		CBM8	th. 0,8 mm	0178 746.15		CBM8	th. 0,8 mm	0178 746.15					
				PC61	10 poles	0163 311.22		PC61	10 poles	0163 311.22					
				AD2,5		0114 205.20		AD2,5		0114 205.20					
				DCJ	yellow	0173 059.03		DCJ	yellow	0173 059.03					
(10) Sides of block (6) RC510 on blade Note : (1) End sections and separators snapped on rails.				(11) Sides of block (6) RC810 on blade				(11) Sides of block							