

# Feed through and ground Terminal blocks

Screw clamp  DIN 1-3

## M 10/10 - 10 mm<sup>2</sup> blocks - 10 mm .394" spacing

### Characteristics

		IEC NFC DIN	UL	CSA
Wire size mm <sup>2</sup> / AWG	Solid	0.5 - 16	20-6 AWG	18-6 AWG
	Stranded	0.5 - 10		
Voltage	V	800	600	600
Current	A	57	65	70
Short circuit current (M 10/10.PI)	A / s	1200A/1s		
Rated wire size	mm <sup>2</sup> / AWG	10 mm <sup>2</sup>	6 AWG	6 AWG
Wire stripping length	mm / inches	12 mm / .47"		
Recommended torque	Nm / lb.in	1.2-1.4 Nm / 10.6-12.4 lb.in		

### Selection

Description	Type	Order P/N	Packaging Weight kg
Standard block grey	<input type="checkbox"/> M 10/10	1SNA 115 120 R1700	50
Standard block blue	<input type="checkbox"/> M 10/10.N	1SNA 125 120 R1100	50
Standard block yellow	<input type="checkbox"/> M 10/10	1SNA 105 120 R2600	50
Standard block beige V0	<input type="checkbox"/> M 10/10.V0	1SNA 195 120 R1000	50
Ground block yellow body/ green marking (without rail contact)	<input type="checkbox"/> M 10/10.PI	1SNA 165 452 R2200	50

### Accessories

End stop		BAM 9.1 mm	1SNA 103 002 R2600	50
End section	grey	<input type="checkbox"/> FEM6 2.8 mm	1SNA 118 368 R1600	20
	blue	<input type="checkbox"/> FEM6 2.8 mm	1SNA 128 368 R1000	20
	orange	<input type="checkbox"/> FEM6 2.8 mm	1SNA 103 126 R1600	20
	yellow	<input type="checkbox"/> FEM6 2.8 mm	1SNA 103 062 R2100	20
	green	<input type="checkbox"/> FEM6 2.8 mm	1SNA 103 125 R1500	20
Separator end section	grey	<input type="checkbox"/> SCF6 3 mm	1SNA 118 707 R0300	20
Assembled jumper bar (with IP20 protection)	2 poles	BJMI10 57 A	1SNA 176 675 R0400	10
	3 poles	BJMI10 57 A	1SNA 176 676 R0500	10
	4 poles	BJMI10 57 A	1SNA 176 677 R0600	10
	5 poles	BJMI10 57 A	1SNA 176 678 R1700	10
	10 poles	BJMI10 57 A	1SNA 176 679 R1000	10

## M 10/10.P - 10 mm<sup>2</sup> ground block with rail contact - 10 mm .394" spacing

### Characteristics


		IEC NFC DIN	UL	CSA
Wire size mm <sup>2</sup> / AWG	Solid	0.5 - 16	20-6 AWG	18-6 AWG
	Stranded	0.5 - 10		
Short circuit current	A / s	1200A/1s		
Rated wire size	mm <sup>2</sup> / AWG	10 mm <sup>2</sup>	6 AWG	6 AWG
Wire stripping length	mm / inches	12 mm / .47"		
Recommended torque	Nm / lb.in	1.2-1.4 Nm / 10.6-12.4 lb.in		

### Selection

Description	Type	Order P/N	Packaging Weight kg
Ground block V2 green/yellow	<input type="checkbox"/> M 10/10.P	1SNA 165 115 R1000	50
Ground block V0 green/yellow	<input type="checkbox"/> M 10/10.P V0	1SNA 195 115 R0700	50

### Accessories

Separator end section	grey	<input type="checkbox"/> SCFM6 3 mm	1SNA 114 825 R0500	20
-----------------------	------	-------------------------------------	--------------------	----




M 10/10



BAM




FEM6




SCF6



BJMI10



M 10/10.P



SCFM6