

M 300/42.FF					M 35/26.AF					M 70/31.AF				
Spacing 42 mm (1.65")					Spacing 26 mm (1.02")					Spacing 31 mm (1.22")				
<p>2 studs M10 linked by 1 removable bar 31,5 x 5 mm</p>					<p>1 stud M6 1 wire-clamp with HM6 screw</p>					<p>1 stud M8 1 wire-clamp with HM8 screw</p>				
<p>Color Type Part numbers</p> <p>Grey M 300/42.FF 1SNA 115 149 R2000</p> <p>Beige V0 M 300/42.FF.V0 1SNA 195 149 R2100</p>					<p>Color Type Part number</p> <p>Grey M 35/26.AF 1SNA 115 139 R1600</p>					<p>Color Type Part number</p> <p>Grey M 70/31.AF 1SNA 115 142 R1100</p>				
Characteristics					Characteristics					Characteristics				
Wire size					Wire size					Wire size				
	DIN	NFC	UL	CSA		DIN	NFC	UL	CSA		DIN	NFC	UL	CSA
Lug	6-150 mm ²	50-150 mm ²	1/0-500 MCM	500 MCM max	Lug	2.5-50 mm ²	4-35 mm ²	10-2 AWG	4 AWG max.	Lug	2.5-70 mm ²	6-70 mm ²	8-0 AWG	6-0 AWG
Bar	32 x 8 mm		1.26" x .32"		Bar	16 x 4 mm		.63" x .16"		Bar	20 x 5 mm		.78" x .20"	
Wire-clamp					Wire-clamp	6-50 mm ²	6-50 mm ²	14-2 AWG	10-4 AWG	Wire-clamp	6-70 mm ²	6-70 mm ²	8-0 AWG	6-0 AWG
Voltage	IEC	IEC			Voltage	IEC	IEC			Voltage	IEC	IEC		
V _~ Without partition	1000	1000	600	600	V _~ Without partition	1000-1200	1000	600	600	V _~ Without partition	1000-1200	1000	600	600
V _~ With partition	1000	1000	600	600	V _~ With partition	1000-1200	1000	600	600	V _~ With partition	1000-1200	1000	600	600
Pulse	12 kV	12 kV			Pulse	8 kV	8 kV			Pulse	8 kV	8 kV		
Pollution degree	3	3			Pollution degree	3	3			Pollution degree	3	3		
Current	DIN	NFC			Current	DIN	NFC			Current	DIN	NFC		
Rated	265 A	269 A	230 A	550 A	Rated	115 A	101 A	115 A	125 A	Rated	178 A	150 A	150 A	200 A
Wire-size					Wire-size					Wire-size				
Rated	95 mm ²	120 mm ²	500 MCM	500 MCM	Rated	25 mm ²	25 mm ²	2 AWG	4 AWG	Rated	50 mm ²	50 mm ²	1/0 AWG	0 AWG
Lug	Central bolt	Wire-clamp	Wire stripping length		Lug	Central bolt	Wire-clamp	Wire stripping length		Lug	Central bolt	Wire-clamp	Wire stripping length	
H 16 mm					H 10 mm		H 10 mm	19 mm .75"		H 13 mm		H 13 mm	22 mm .87"	
10 Nm 87 lb.in					4,5 Nm 39 lb.in		4,5 Nm 39 lb.in			6 Nm 52 lb.in		6 Nm 52 lb.in		
Type	Part numbers				Type	Part numbers				Type	Part numbers			
BAEH	th. 12 mm	1SNA 116 934 R0400			BAEH	th. 12 mm	1SNA 116 934 R0400			BAEH	th. 12 mm	1SNA 116 934 R0400		
BADH	th. 12 mm	1SNA 116 900 R2700			BADH	th. 12 mm	1SNA 116 900 R2700			BADH	th. 12 mm	1SNA 116 900 R2700		
BAMH	th. 9,1 mm	1SNA 114 836 R0000			BAMH	th. 9,1 mm	1SNA 114 836 R0000			BAMH	th. 9,1 mm	1SNA 114 836 R0000		
ECP42		1SNA 113 692 R1700			ECP26		1SNA 113 689 R2400			ECP31		1SNA 113 690 R2100		
CPP421	1 block	1SNA 168 208 R2100			CPP261	1 block	1SNA 168 202 R1300			CPP311	1 block	1SNA 168 204 R1500		
CPP422	2 blocks	1SNA 168 207 R1000			CPP262	2 blocks	1SNA 168 201 R1200			CPP312	2 blocks	1SNA 168 203 R1400		
CPP423	3 blocks	1SNA 163 424 R1400			CPP263	3 blocks	1SNA 163 403 R2000			CPP313	3 blocks	1SNA 163 409 R0600		
CPU42		1SNA 116 515 R0000			CPU26		1SNA 114 882 R0700			CPU31		1SNA 114 996 R0100		
<p>15 for ECP 6 for CPU</p>					<p>15 for ECP and wire-clamp 6 for CPU</p>					<p>15 for ECP and wire-clamp 6 for CPU</p>				