



## General Information


The following information must be strictly adhered to in order to guarantee the terminal block electrical, mechanical and environmental performance.

Protection		<b>IP 20</b>	<i>NEMA 1</i>		
Rail		<b>DIN3-TH35</b>			
Wire stripping length		<b>17 mm</b>	<i>0.669 in</i>		
		Screw clamp		Screw rail contact (Maximum value)	
Operating tool		<b>Flat screwdriver</b>			
		<b>6.5 mm</b>	<i>0.256 in</i>	<b>5.5 mm</b>	<i>0.217 in</i>
Torque		<b>2.65 Nm</b> <b>± 0.15 Nm</b>	<i>23.5 lb.in</i> <i>± 1.33 lb.in</i>	<b>1.6 Nm</b> <b>± 0.15 Nm</b>	<i>14.2 lb.in</i> <i>± 1.33 lb.in</i>
Mechanical endurance of disconnect system					

## Material Specifications

Insulating material	<b>Polyamide</b>
IRC	<b>600 V</b>
Flammability	UL94
	<b>NF F 16 101</b>
	Needle flame test IEC 60695-11-5
	<b>V0</b>
	<b>I2F2</b>
	<b>Compliant</b>

## Connecting capacity per clamp

1 Rigid conductor		<b>6-35 mm<sup>2</sup></b>		<i>10-0 AWG</i>
1 Flexible conductor without ferrule		<b>6-35 mm<sup>2</sup></b>		<i>10-0 AWG</i>
1 Flexible conductor with ferrule				
Ferrule maximum outer diameter		<b>14 mm</b>	<i>0.551 in</i>	

## Multi Connecting capacity per clamp

2 Rigid conductors				
2 Flexible conductors without ferrule				
2 Flexible conductors with twin ferrule				

Don't mix **solid and flexible** conductors in the same clamp

Don't mix **solid or flexible** conductors of different sizes in the same clamp

The "Connecting capacity with ferrule " data is guaranteed with ABB crimping tool PS-3

## Cross section

Rated cross section		<b>35 mm<sup>2</sup></b>		<i>0 AWG</i>
Maximum Cross section	<b>Manufacturer data</b>	<b>35 mm<sup>2</sup></b>	<i>Manufacturer data</i>	<i>0 AWG</i>

Gauge **A9 / 10 mm / 0.394 in / IEC 60947-7-1**

## Electrical characteristics

### Current

Rated current		IEC 60947-7-1	
	Field and factory wiring Cat.2	UL 1059	
	Factory wiring Cat.1	UL 1059	
		CSA-C-22.2 n° 158	
Rated short-time withstand current 1 s (I <sub>cw</sub> )			<b>4200 A</b>
Short-time withstand current	0.5 s	Manufacturer data	
	5 s	Manufacturer data	
	10 s	Manufacturer data	
	30 s	Manufacturer data	
	1 mn	Manufacturer data	
Rated short circuit withstand		CSA-C-22.2 n° 158	
Max. current (45° temperature increase) / Max. cross section (mm <sup>2</sup> )		Manufacturer data	<b>35 mm<sup>2</sup></b>
Maximum short circuit current (1s)		Manufacturer data	<b>4200 A</b>

**Short Circuit Current Rating (SCCR) SA UL 1059 supplement**

SCCR UL 1059

With the following configurations:

Maximum voltage
Suitable conductor wire range
Fuse rating
Fuse designation
Fuse manufacturer name
Fuse type
Short circuit current



**Voltage**

Rated voltage	IEC 60947-1	
Rated voltage	UL 1059	
Use Group	UL 1059	<b>C</b>
Rated voltage	CSA-C-22.2 n° 158	
Rated voltage Ex e	IEC/EN 60079-11	
Rated impulse withstand voltage		<b>8000 V</b>
Dielectric test voltage		<b>2200 V</b>
Pollution degree	IEC 60947-1	<b>3</b>
Overvoltage category	IEC 60947-1	<b>III</b>

**Dissipated power**

Maximum dissipated power at rated current	IEC	
---	-----	--

**Rated power dissipation at an ambient temperature of 23 °C - IEC 60947-7-3**

Overload and short-circuit protection Separate arrangement	 <p>1 fuse and 4 feed-through blocks</p>	
Exclusive short-circuit protection Separate arrangement		
Overload and short-circuit protection Compound arrangement	 <p>5 fuse blocks</p>	
Exclusive short-circuit protection Compound arrangement		

**Temperature range**

Ambient temperature min/max	Storage		<b>-55 +110 °C</b>	<i>-67 +230 F</i>
	Installing		<b>-5 +40 °C</b>	<i>-23 +104 F</i>
	Service	IEC 60068-2-1	<b>-55 +110 °C</b>	<i>-67 +230 F</i>
		EN 60079-7	<b>-55 +85 °C</b>	

Current Derating curve for continuous service temperature

## Environmental Characteristics

### Additional climatic tests

Dry heat	Conditions	IEC 60068-2-2	<b>Compliant</b>	
		Temperature	<b>+100 °C</b>	
		Duration of test	<b>96 h</b>	
Cyclic damp heat	Conditions	IEC 60068-2-30	<b>Compliant</b>	
		Temperature	<b>+55 °C</b>	
		Number of cycles	<b>2</b>	
Cold	Conditions	IEC 60068-2-1	<b>Compliant</b>	
		Temperature	<b>-40 °C</b>	
		Duration of test	<b>96 h</b>	
Z/ABDM climatic sequence	Conditions	IEC 60068-2-61	<b>Compliant</b>	
		Dry heat Duration of test / Temperature	<b>16 h</b>	<b>+85 °C</b>
		Cyclic damp heat Number of cycles / Temperature	<b>1</b>	<b>+55 °C</b>
		Cold Duration of test / Temperature	<b>2 h</b>	<b>-25 °C</b>

### Corrosion

Salt mist	Conditions	IEC 60068-2-11	<b>Compliant</b>	
		Duration of test	<b>96 h</b>	
		Concentration	<b>5 %</b>	
SO <sub>2</sub>	Conditions	ISO 6988	<b>Compliant</b>	
		Duration of test	<b>48 h</b>	
		Concentration	<b>0.2 dm<sup>3</sup></b>	
Sulfur dioxide	Conditions	IEC 60068-2-42		
Hydrogen sulfur	Conditions	IEC 60068-2-43		
Flowing mixed gas corrosion test	Conditions	IEC 60068-2-60		
		Number of the test method		
		Duration of test		

### Vibrations

Vibrations	Conditions	IEC 60068-2-6	<b>Compliant</b>			
		Frequency range	<b>10-55 Hz</b>			
		Number of cycles	<b>10</b>			
		Amplitude				
		Acceleration	<b>10 m/s<sup>2</sup></b>			
Random vibrations and climatic sequence	Conditions	IEC 60068-2-64				
		Duration of test				
		Frequency range				
		Acceleration				
		Climatic cycles				
		Step 1 -> Temperature / Duration of test				
Step 2 -> Temperature / Duration of test						
		Temperature variation per minute				

**ZS35-PE Terminal Block Accessories Compatibility**

Description	Type	Order Code	Pack <sup>(ing)</sup> pieces	Weight g (1 pce)	Technical Datasheet PDF
<b>1</b> End Stops	<b>BAZH1</b>	<b>1SNK 900 102 R0000</b>	20	23.90	<b>1SNK 160 026 D0201</b>
<b>2</b> Circuit Separators	<b>CS-R1</b>	<b>1SNK 900 103 R0000</b>	20	5.20	<b>1SNK 160 018 D0201</b>
<b>3</b> Protecting Covers	<b>CO</b>	<b>1SNK 900 604 R0000</b>	1	300.00	<b>1SNK 160 020 D0201</b>
<b>4</b> Protecting Cover Kits	<b>KCO</b>	<b>1SNK 900 624 R0000</b>	1	47,8	<b>1SNK 160 028 D0201</b>
<b>5</b> Terminal Block Markers	<b>MC812</b>	<b>1SNK 160 000 R0000</b>	22	0.09	<b>1SNK 160 009 D0201</b>
	<b>UMH</b>	<b>1SNK 900 611 R0000</b>	10	0.20	<b>1SNK 160 001 D0201</b>
	<b>PROCAP8</b>	<b>1SNK 900 613 R0000</b>	20	1.00	<b>1SNK 160 013 D0201</b>
	<b>SAT8</b>	<b>1SNK 900 616 R0000</b>	5	6.00	<b>1SNK 160 013 D0201</b>