





General Information

The following information must be strictly adhered to in order to guarantee the terminal block electrical, mechanical and environmental performance.

Protection		IP 10	<i>NEMA 1</i>		
Rail		DIN3-TH35			
Wire stripping length		26 mm	<i>1.023 in</i>		
		Screw clamp		Screw rail contact (Maximum value)	
Operating tool		Allen Key			
		6 mm	<i>0.236 in</i>		
Torque		9.25 Nm ± 0.25 Nm	<i>81.7 lb.in</i> <i>± 2.2 lb.in</i>	± 0.25 Nm	<i>± 2.2 lb.in</i>
Mechanical endurance of disconnect system					

Material Specifications

Insulating material	Polyamide
IRC	600 V
Flammability	UL94
	NF F 16 101
	Needle flame test IEC 60695-11-5
	V0
	I2F2
	Compliant

Connecting capacity per clamp

1 Rigid conductor		35-120 mm²		<i>2-0000 AWG</i>
1 Flexible conductor without ferrule		35-95 mm²		<i>2-000 AWG</i>
1 Flexible conductor with ferrule				

Ferrule maximum outer diameter



Multi Connecting capacity per clamp

2 Rigid conductors				<i>25-35 AWG</i>
2 Flexible conductors without ferrule				<i>25-35 AWG</i>
2 Flexible conductors with twin ferrule				

Don't mix **solid and flexible** conductors **in the same clamp**

Don't mix **solid or flexible** conductors of different sizes **in the same clamp**

The "Connecting capacity with ferrule " data is guaranteed with ABB crimping tool PS-3

Cross section

Rated cross section		95 mm²		<i>000 AWG</i>
Maximum Cross section	Manufacturer data	95 mm²	<i>Manufacturer data</i>	<i>000 AWG</i>

Gauge **B12 / 16 mm / 0.630 in / IEC 60947-7-1**

Electrical characteristics

Current

Rated current		IEC 60947-7-1	232 A
	Field and factory wiring Cat.2	UL 1059	230 A
	Factory wiring Cat.1	UL 1059	230 A
		CSA-C-22.2 n° 158	
Rated short-time withstand current 1 s (I _{cw})			11400 A
Short-time withstand current	0.5 s	Manufacturer data	
	5 s	Manufacturer data	
	10 s	Manufacturer data	
	30 s	Manufacturer data	
	1 mn	Manufacturer data	
Rated short circuit withstand		CSA-C-22.2 n° 158	
Max. current (45° temperature increase) / Max. cross section (mm ²)		Manufacturer data	232 A 95 mm²
Maximum short circuit current (1s)		Manufacturer data	11400 A

Short Circuit Current Rating (SCCR) SA UL 1059 supplement

SCCR UL 1059

With the following configurations:

Maximum voltage	
Suitable conductor wire range	
Fuse rating	
Fuse designation	
Fuse manufacturer name	
Fuse type	
Short circuit current	



Voltage

Rated voltage	IEC 60947-1	1000 V
Rated voltage	UL 1059	600 V
Use Group	UL 1059	C
Rated voltage	CSA-C-22.2 n° 158	600 V
Rated voltage Ex e	IEC/EN 60079-11	630 V
Rated impulse withstand voltage		8000 V
Dielectric test voltage		3500 V
Pollution degree	IEC 60947-1	3
Overtoltage category	IEC 60947-1	III

Dissipated power

Maximum dissipated power at rated current	IEC	7.4 W
---	-----	--------------


Rated power dissipation at an ambient temperature of 23 °C - IEC 60947-7-3

Overload and short-circuit protection Separate arrangement		
Exclusive short-circuit protection Separate arrangement	1 fuse and 4 feed-through blocks	
Overload and short-circuit protection Compound arrangement		
Exclusive short-circuit protection Compound arrangement	5 fuse blocks	

Temperature range

Ambient temperature min/max	Storage	-55 +110 °C	-67 +230 F
	Installing	-5 +40 °C	-23 +104 F
	Service	IEC 60068-2-1	-55 +110 °C
		EN 60079-7	-55 +85 °C

Current Derating curve for continuous service temperature



Environmental Characteristics

Additional climatic tests

Dry heat	Conditions	IEC 60068-2-2	Compliant	
		Temperature	+100 °C	
		Duration of test	96 h	
Cyclic damp heat	Conditions	IEC 60068-2-30	Compliant	
		Temperature	+55 °C	
		Number of cycles	2	
Cold	Conditions	IEC 60068-2-1	Compliant	
		Temperature	-40 °C	
		Duration of test	96 h	
Z/ABDM climatic sequence	Conditions	IEC 60068-2-61	Compliant	
		Dry heat Duration of test / Temperature	16 h	+85 °C
		Cyclic damp heat Number of cycles / Temperature	1	+55 °C
		Cold Duration of test / Temperature	2 h	-25 °C

Corrosion

Salt mist	Conditions	IEC 60068-2-11	Compliant	
		Duration of test	96 h	
		Concentration	5 %	
SO ₂	Conditions	ISO 6988	Compliant	
		Duration of test	48 h	
		Concentration	0.2 dm³	
Sulfur dioxide	Conditions	IEC 60068-2-42		
Hydrogen sulfur	Conditions	IEC 60068-2-43		
Flowing mixed gas corrosion test	Conditions	IEC 60068-2-60		
		Number of the test method		
		Duration of test		

Vibrations

Vibrations	Conditions	IEC 60068-2-6	Compliant			
		Frequency range	10-55 Hz			
		Number of cycles	10			
		Amplitude				
		Acceleration	10 m/s²			
Random vibrations and climatic sequence	Conditions	IEC 60068-2-64				
		Duration of test				
		Frequency range				
		Acceleration				
		Climatic cycles				
		Step 1 -> Temperature / Duration of test				
Step 2 -> Temperature / Duration of test						
		Temperature variation per minute				

ZS95 Terminal Block Accessories Compatibility

Description	Type	Order Code	Pack ^(ing) pieces	Weight g (1 pce)	Technical Datasheet PDF
1 End Stops	BAZH1	1SNK 900 102 R0000	20	23.90	1SNK 160 026 D0201
2 Jumper Bars	JB26-2	1SNK 926 302 R0000	5	41.20	1SNK 160 034 D0201
	JB26-3	1SNK 926 303 R0000	5	65.70	1SNK 160 034 D0201
	JB26-5	1SNK 926 305 R0000	5	115.70	1SNK 160 034 D0201
	JB26-10	1SNK 926 310 R0000	5	241.50	1SNK 160 034 D0201
3 Terminal Block Markers	MC812	1SNK 160 000 R0000	22	0.09	1SNK 160 009 D0201
	UMH	1SNK 900 611 R0000	10	0.20	1SNK 160 001 D0201
	PROCAP8	1SNK 900 613 R0000	20	1.00	1SNK 160 013 D0201
	SAT8	1SNK 900 616 R0000	5	6.00	1SNK 160 013 D0201