



#### General ordering data

|                  |  |
|------------------|--|
| Order No.        | 9994360000   |
| Part designation | LM5.08/6/135 3.5 SW  |
| Version          | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 6, 135°, Box |
| EAN              | 4032248377046  |
| Qty              | 50 pc(s).  |

#### System parameters

|                                 |                          |
|---------------------------------|--------------------------|
| Series                          | LM series                |
| Conductor connection system     | Clamping yoke connection |
| Fitted to PCB                   | Soldered connection      |
| Outgoing direction of conductor | 135°                     |
| Pitch                           | 5.08 mm                  |
| Pitch in inch                   | 0.2 inch                 |
| Number of poles                 | 6                        |
| Fitted by customer              | yes                      |
| Max. adjacent poles per row     | 24                       |
| No. of rows                     | 1                        |
| Length of soldering post        | 3.5 mm                   |
| Dia. of fitting hole            | 1.3 mm                   |
| Fitting hole tolerance          | + 0.1 mm                 |

#### System parameters

|   |                        |
|---|------------------------|
| No. of solder pins per pole               | 1                      |
| Screwdriver blade                         | 0.6 x 3.5              |
| Screwdriver blade standard                | DIN 5264               |
| Tightening torque, min.                   | 0.4 Nm                 |
| Tightening torque, max.                   | 0.5 Nm                 |
| Clamping screw                            | M 2.5                  |
| Stripping length                          | 6 mm                   |
| L1 in mm                                  | 25.4 mm                |
| L1 in inch                                | 1 inch                 |
| Electric shock protection to DIN VDE 0470 | IP 20                  |
| Electric shock protection to DIN VDE 0470 | Safe from finger touch |

#### Material data

|                               |                  |
|-------------------------------|------------------|
| Insulation material           | Wemid (PA)       |
| Colour                        | black            |
| Description of plastic colour | ähnlich RAL 9011 |
| Insulating material group     | I                |
| UL 94 combustibility class    | V-0              |
| CTI                           | >= 600           |
| Temperature of glow-wire test | 750 °C           |
| Duration of glow-wire test    | 30 S             |
| Contact base material         | Cu alloy         |
| Contact surface               | tinned           |
| Storage temperature, min.     | -25 °C           |
| Storage temperature, max.     | 55 °C            |

#### Connectable conductors

|   |                        |
|---|------------------------|
| Clamping range, min.                            | 0.2 mm <sup>2</sup>    |
| Clamping range, max.                            | 2.5 mm <sup>2</sup>    |
| AWG, min.                                       | 24                     |
| AWG, max.                                       | 14                     |
| O.D. of conductor insulation, max.              | 2.9 mm                 |
| Solid, min. H05(07) V-U                         | 0.2 mm <sup>2</sup>    |
| Solid, max. H05(07) V-U                         | 2.5 mm <sup>2</sup>    |
| fine-stranded, min. H05(07) V-U                 | 0.2 mm <sup>2</sup>    |
| fine-stranded, max. H05(07) V-U                 | 1.5 mm <sup>2</sup>    |
| Wire end ferrule , DIN 46 228/1, min.           | 0.25 mm <sup>2</sup>   |
| Wire end ferrule , DIN 46 228/1, max.           | 1.5 mm <sup>2</sup>    |
| w. plastic collar ferrule, DIN 46228 pt 4, min. | 0.25 mm <sup>2</sup>   |
| w. plastic collar ferrule, DIN 46228 pt 4, max. | 1.5 mm <sup>2</sup>    |
| Gauge to EN 60999 a x b; ø                      | 2.4 mm x 1.5 mm; 1.9mm |

#### DIN IEC rating data

|  |        |
|--|--------|
| Rated current, min. No. pins (Tu=20°C)                       | 17.5 A |
| Rated current, max. No. pins (Tu=20°C)                       | 16 A   |
| Rated current, min. No. pins (Tu=40°C)                       | 17.5 A |
| Rated current, max. No. pins (Tu=40°C)                       | 14.2 A |
| Rated voltage for overvoltage class/pollution severity II/2  | 630 V  |
| Rated voltage for overvoltage class/pollution severity III/2 | 320 V  |

#### DIN IEC rating data

|  |                   |
|--|-------------------|
| Rated voltage for overvoltage class/pollution severity III/3                   | 250 V             |
| Rated impulse withstand voltage for overvoltage class/pollution severity II/2  | 4 kV              |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/2 | 4 kV              |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/3 | 4 kV              |
| Short-time withstand current resistance  | 3 x 1s with 120 A |

#### CSA rating data

|                                    |       |
|------------------------------------|-------|
| Rated voltage                      | 300 V |
| Rated current                      | 10 A  |
| AWG conductor (field wiring), min. | 24    |
| AWG conductor (field wiring), max. | 14    |

#### UL 1059 rating data

|                                    |       |
|------------------------------------|-------|
| Rated voltage                      | 300 V |
| Rated current                      | 10 A  |
| AWG conductor (field wiring), min. | 24    |
| AWG conductor (field wiring), max. | 14    |

#### Approvals

Approval body



#### Downloads

|                                       |        |
|---------------------------------------|--------|
| CAD Library (P-CAD Format - ASCII)    | LM.LIA |
| CAD Library (P-CAD Format - Standard) | LM.lib |

#### Classifications

|            |    |
|------------|----|
| ETIM 2.0   | NK |
| eClass 4.1 | NK |
| eClass 5.0 | NK |
| eClass 5.1 | NK |

#### Similar products

| Order No.  | Part designation     | Version   |
|------------|----------------------|---|
| 9994660000 | LM5.08/15/135 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 15, 135°, Box |
| 9994740000 | LM5.08/23/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 23, 135°, Box |
| 1915460000 | LM 5.08/3/135 GR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 3, 135°, Box  |
| 9994490000 | LM5.08/19/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 19, 135°, Box |
| 1915390000 | LM5.08/8/135 GN      | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 8, 135°, Box  |
| 9994520000 | LM5.08/22/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 22, 135°, Box |
| 9994500000 | LM5.08/20/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 20, 135°, Box |
| 9994460000 | LM5.08/16/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 16, 135°, Box |
| 1915570000 | LM 5.08/9/135 GR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 9, 135°, Box  |
| 9994670000 | LM5.08/16/135 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 16, 135°, Box |
| 9994680000 | LM5.08/17/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 17, 135°, Box |
| 1915360000 | LM5.08/5/135 GN      | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 5, 135°, Box  |
| 1915440000 | LM 5.08/2/135 GR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 2, 135°, Box  |
| 1915400000 | LM5.08/9/135 GN      | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 9, 135°, Box  |
| 9994640000 | LM5.08/13/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 13, 135°, Box |
| 9994480000 | LM5.08/18/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 18, 135°, Box |
| 9994630000 | LM5.08/12/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 12, 135°, Box |

|            |                      |   |
|------------|----------------------|---|
| 9994350000 | LM5.08/5/135 3.5 SW  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 5, 135°, Box  |
| 1915370000 | LM5.08/6/135 GN      | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 6, 135°, Box  |
| 9994390000 | LM5.08/9/135 3.5 SW  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 9, 135°, Box  |
| 9994370000 | LM5.08/7/135 3.5 SW  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 7, 135°, Box  |
| 9994420000 | LM5.08/12/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 12, 135°, Box |
| 9994580000 | LM5.08/7/135 3.5OR   | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 7, 135°, Box  |
| 9994750000 | LM5.08/24/135 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 24, 135°, Box |
| 9994730000 | LM5.08/22/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 22, 135°, Box |
| 1716060000 | LM5.08/2/135 SW      | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 2, 135°, Box  |
| 9994550000 | LM5.08/4/135 3.5OR   | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 4, 135°, Box  |
| 9994430000 | LM5.08/13/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 13, 135°, Box |
| 9994400000 | LM5.08/10/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 10, 135°, Box |
| 9994720000 | LM5.08/21/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 21, 135°, Box |
| 9994620000 | LM5.08/11/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 11, 135°, Box |
| 1716070000 | LM5.08/3/135 SW      | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 3, 135°, Box  |
| 1915420000 | LM5.08/11/135 GN     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 11, 135°, Box |
| 9994440000 | LM5.08/14/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 14, 135°, Box |

|            |                      |   |
|------------|----------------------|---|
| 1716130000 | LM5.08/3/135 OR      | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 3, 135°, Box  |
| 1915540000 | LM 5.08/6/135 GR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 6, 135°, Box  |
| 1716190000 | LM5.08/3/135 GN      | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 3, 135°, Box  |
| 1915600000 | LM 5.08/12/135 GR    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 12, 135°, Box |
| 1915430000 | LM5.08/12/135 GN     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 12, 135°, Box |
| 1716120000 | LM5.08/2/135 OR      | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 2, 135°, Box  |
| 9994470000 | LM5.08/17/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 17, 135°, Box |
| 1915550000 | LM 5.08/7/135 GR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 7, 135°, Box  |
| 1915350000 | LM5.08/4/135 GN      | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 4, 135°, Box  |
| 1716180000 | LM5.08/2/135 GN      | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 2, 135°, Box  |
| 1915490000 | LM 5.08/4/135 GR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 4, 135°, Box  |
| 9994340000 | LM5.08/4/135 3.5 SW  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 4, 135°, Box  |
| 9994380000 | LM5.08/8/135 3.5 SW  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 8, 135°, Box  |
| 9994700000 | LM5.08/19/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 19, 135°, Box |
| 9994360000 | LM5.08/6/135 3.5 SW  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 6, 135°, Box  |
| 1915410000 | LM5.08/10/135 GN     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 10, 135°, Box |
| 9994710000 | LM5.08/20/135 3.5 OR | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 20, 135°, Box |

|            |                      |   |
|------------|----------------------|---|
| 9994560000 | LM5.08/5/135 3.5OR   | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 5, 135°, Box  |
| 1915530000 | LM 5.08/5/135 GR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 5, 135°, Box  |
| 1915560000 | LM 5.08/8/135 GR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 8, 135°, Box  |
| 9994570000 | LM5.08/6/135 3.5OR   | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 6, 135°, Box  |
| 9994590000 | LM5.08/8/135 3.5OR   | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 8, 135°, Box  |
| 9994410000 | LM5.08/11/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 11, 135°, Box |
| 9994650000 | LM5.08/14/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 14, 135°, Box |
| 9994610000 | LM5.08/10/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 10, 135°, Box |
| 9994600000 | LM5.08/9/135 3.5OR   | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 9, 135°, Box  |
| 9994530000 | LM5.08/23/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 23, 135°, Box |
| 1915380000 | LM5.08/7/135 GN      | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 7, 135°, Box  |
| 9994540000 | LM5.08/24/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 24, 135°, Box |
| 9994450000 | LM5.08/15/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 15, 135°, Box |
| 9994690000 | LM5.08/18/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 18, 135°, Box |
| 1915590000 | LM 5.08/11/135 GR    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 11, 135°, Box |
| 1915580000 | LM 5.08/10/135 GR    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 10, 135°, Box |
| 9994510000 | LM5.08/21/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.08 mm, Number of poles: 21, 135°, Box |