M 120/35.F

Spacing 35 mm *(1.38")*



1 stud M8

Color	Type	Part number
Grey	**M 120/35.F**	**1SNA 115 147 R1600**

Characteristics

Wire size

	DIN	NFC	UL	CSA
Lug	2,5-70 mm²	6-95 mm²	2-250 MCM	000 AWG max.
Bar		25 x 5 mm	*1" x .20"*	
Wire-clamp				

Voltage		IEC	IEC		
V~=	Without partition	1000	1000	600	600
	With partition	1000	1000	600	600
Pulse		8 kV	8 kV		
Pollution degree		3	3		

Current	DIN	NFC		
Rated	150 A	192 A	255 A	270 A

Wire-size				
Rated	50 mm²	70 mm²	250 MCM	000 AWG

Lug	Central bolt	Wire-clamp	Wire stripping length
H 13 mm			
6 Nm *52 lb.in*			

Type			Part numbers
BAEH		th. 12 mm	1SNA 116 934 R0400
BADH		th. 12 mm	1SNA 116 900 R2700
BAMH		th. 9,1 mm	1SNA 114 836 R0000
ECP35			1SNA 113 691 R1600
CPP351		1 block	1SNA 168 206 R1700
CPP352		2 blocks	1SNA 168 205 R1600
CPP353		3 blocks	1SNA 163 418 R2600
CPU35			1SNA 116 514 R0700

(15) for ECP (6) for CPU

M 300/42.F

Spacing 42 mm *(1.65")*



1 stud M10

Color	Type	Part number
Grey	**M 300/42.F**	**1SNA 115 150 R2500**

Characteristics

Wire size

	DIN	NFC	UL	CSA
Lug	6-150 mm²	50-150 mm²	0-500 MCM	500 MCM
Bar		32 x 8 mm	*1.26" x .32"*	
Wire-clamp				

Voltage		IEC	IEC		
V~=	Without partition	1000	1000	600	600
	With partition	1000	1000	600	600
Pulse		8 kV	8 kV		
Pollution degree		3	3		

Current	DIN	NFC		
Rated	269 A	269 A	230 A	550 A

Wire-size				
Rated	120 mm²	120 mm²	500 MCM	500 MCM

Lug	Central bolt	Wire-clamp	Wire stripping length
H 16 mm			
10 Nm *87 lb.in*			

Type			Part numbers
BAEH		th. 12 mm	1SNA 116 934 R0400
BADH		th. 12 mm	1SNA 116 900 R2700
BAMH		th. 9,1 mm	1SNA 114 836 R0000
ECP42			1SNA 113 692 R1700
CPP421		1 block	1SNA 168 208 R2100
CPP422		2 blocks	1SNA 168 207 R1000
CPP423		3 blocks	1SNA 163 424 R1400
CPU42			1SNA 116 515 R0000

(15) for ECP (6) for CPU

M 35/26.FF

END OF SERIES

Spacing 26 mm *(1.02")*



2 studs M6 linked by
1 removable bar 15 x 4 mm

Color	Type	Part numbers
Grey	**M 35/26.FF**	**1SNA 115 140 R2300**
Beige V0	**M 35/26.FF.V0**	**1SNA 195 140 R2400**

Characteristics

Wire size

	DIN	NFC	UL	CSA
Lug	2,5-50 mm²	4-35 mm²	10-2 AWG	4 AWG max.
Bar		16 x 4 mm	*.63" x .16"*	
Wire-clamp				

Voltage		IEC	IEC		
V~=	Without partition	1000	1000	600	600
	With partition	1000	1000	600	600
Pulse		8 kV	8 kV		
Pollution degree		3	3		

Current	DIN	NFC		
Rated	125 A	101 A	115 A	125 A

Wire-size				
Rated	35 mm²	25 mm²	2 AWG	4 AWG

Lug	Central bolt	Wire-clamp	Wire stripping length
H 10 mm			
4,5 Nm *39 lb.in*			

Type			Part numbers
BAEH		th. 12 mm	1SNA 116 934 R0400
BADH		th. 12 mm	1SNA 116 900 R2700
BAMH		th. 9,1 mm	1SNA 114 836 R0000
ECP26			1SNA 113 689 R2400
CPP261		1 block	1SNA 168 202 R1300
CPP262		2 blocks	1SNA 168 201 R1200
CPP263		3 blocks	1SNA 163 403 R2000
CPU26			1SNA 114 882 R0700

(15) for ECP (6) for CPU

Downloaded from Elcodis.com electronic components distributor