

4 mm dia.  
laboratory equipment

196 017 → 121  
to

Hirschmann

Couplings



Type	KD 10	KUN 10	KUN 30
Order no.	930 109- . . . (see colour index below)*	930 189- . . . (see colour index below)*	931 804- . . . (see colour index below)*
Quantity boxed	100 each	100 each	50 each

Dimensions	KD 10	KUN 10	KUN 30

Description	KD 10	KUN 10	KUN 30
	Insulated coupling with nickel-plated brass tube for two 4 mm dia connectors	Insulated coupling for one 4 mm dia connector and a <b>screw connection</b> up to a maximum cable cross-section of 1.5 mm <sup>2</sup> . Tin-plated brass sleeve. The sleeve is screwed into the insulated handle	Shatter-proof flexible insulated coupling for one 4 mm dia connector and a <b>solder connection</b> up to a maximum cable cross-section of 2.5 mm <sup>2</sup> . Nickel-plated brass sleeve

Technical data			
Type of connection/		screw/	solder/
Connector	ø 4 mm	ø 4 mm	ø 4 mm
Continuous load current	10 A	16 A	30 A
Volume resistance (max.)	5 mΩ	3 mΩ	3 mΩ
Permissible temperature range	-25 °C . . . +70 °C	-25 °C . . . +70 °C	-25 °C . . . +70 °C
Colour index*	black	-100	-100
	red	-101	-101
	blue	-102	-102
	yellow	-103	-103
	green	-104	-104
	assorted clr.		930 274-000 (KUN 10 F)

The version **KUN 10 F** in assorted colours is made up of 20 couplings in each of the colours black, red, blue, yellow and green