



**DO NOT SCALE**  
DIMENSIONS IN mm

**METRIC**

THIRD ANGLE PROJECTION

- NOTES:**
- 1 THIS RECEPTACLE ACCEPTS SIZE 20 REC. CONTACTS.
  - 2 MAXIMUM WIRE INSULATION RECOMMENDED FOR USE WITH THIS RECEPTACLE IS 1,73 DIA. MAX..
  - 3 RETENTION TINES ARE AN INTEGRAL PART OF INSERT.
  - 4 FOLLOWING INSERTION/REMOVAL TOOLS ARE RECOMMENDED FOR USE WITH THESE CONNECTORS:  
 32-28AWG/28-24AWG CONTACTS  
 91067-3 INSERTION/REMOVAL  
 726363-1 INSERTION ONLY  
 24-20AWG CONTACTS  
 726363-1 INSERTION ONLY  
 726364-1 REMOVAL ONLY
- ▲ INSERTS: GLASSFILLED SELF-EXTINGUISHING PBT, COLOR BLACK.
  - ▲ AMP DATE CODE, AMP PART NUMBER, INK STAMPED.
  - ▲ RAISED CAVITY IDENTIFICATION 0,8 HIGH.
  - ▲ RAISED CAVITY IDENTIFICATION NUMBERS ON WIRE SIDE ARE WHITENED FOR 164533-9.

BRIGHT TIN	BRIGHT TIN	STEEL	164533-9 ▲
BRIGHT TIN	BRIGHT TIN	STEEL	164533-4
PLATING FRONT SHELL	PLATING REAR SHELL	MATERIAL SHELLS	PARTNUMBER
-	-	-	<b>CUSTOMER DRAWING</b> FOR REFERENCE ONLY WILL NOT BE UPDATED
-	-	-	© COPYRIGHT 19 - BY AMP HOLLAND B.V. ALL INTERNATIONAL RIGHTS RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN AND/OR PATENTS PENDING. THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
K	SR10-0457-02	KV	24 OCT 02
J	SR10-0382-02	KV	23 AUG 02
H	EH-0314-99	D.K.	W.S. 11 FEB 99
LTR	REVISION RECORD	DR.	CHK. DATE
DR.:	D. KESSLER	CHK.:	W. SOOMERS
DATE:	11 FEB 99	DATE:	-
APP.:	W. SOOMERS	DATE:	-
DWG.No.	C-164533	REV.LTR.	K
SHEET	1 OF 1	A3	

R6-128 (REV.04-91)

8 7 6 5 4 3 2 1