

Other Wiring Products Adapters



HBL5273L



HBL5289



9053A



9054A



HBL2274
Slot End Female Blade End Male

Nylon Convenience Adapters

NEMA Configuration	Male Blade End	Female Slot End	Rating NEMA No.	Catalog Numbers
			20A 125V 5-20R	HBL2270 HBL2274 HBL2129 HBL31CM29*
			15A 125V L5-15R	HBL2271 - - -
			20A 125V L5-20R	HBL2128 - - -

Caution:

Where adapters have different ratings on the blade and slot end the following precautions must be exercised in their use.

- (1) Remember that overcurrent protection is determined by the blade end.
- (2) The use of the adapter should be limited to the lowest rated end of the adapter in order to prevent overheating.
- (3) Adapters are not GFCI protected.

Plug In Adapters

Description	Catalog Numbers
Male end - 2 wire parallel polarized blades, 15A, 125V. Female end - 3 wire 15A, 125V straight slot grounding.	HBL5273L
Male end - 3 wire crow foot 15A, 125V blades. Female end - 3 wire 15A, 125V straight slot grounding.	HBL5289 ♦*
Male end - 3 wire 10A, 250V, 15A, 125V Twist-Lock® blades. Female end - 3 wire 15A, 125V straight slot grounding.	9053A ♦*
Male end - 3 wire 15A, 125V straight blade grounding. Female end - 10A, 250V, 15A 125V Twist-Lock slots.	9054A ♦*

♦Must always be used with a grounded receptacle.

*Not UL Listed.