

Spezifikation für Freigabe / specification for release


Kunde / customer : _____
 Artikelnummer / part number : **74279260**
 Bezeichnung : **Multilayer-SMD-Ferrit**
 description : **Multilayer-SMD-Ferrite**

LF



DATUM / DATE : 2005-12-16

A Mechanische Abmessungen / dimensions:




| Größe / size 0603 | | |
|-------------------|---------------|----|
| A | $1,6 \pm 0,2$ | mm |
| B | $0,8 \pm 0,2$ | mm |
| C | $0,8 \pm 0,2$ | mm |
| D | $0,3 \pm 0,2$ | mm |
| | | |
| | | |
| | | |

B Elektrische Eigenschaften / electrical properties:

| Eigenschaften / properties | Testbedingungen / test conditions | | Wert / value | Einheit / unit | tol. |
|--------------------------------|-----------------------------------|----------|--------------|----------------|------------------------------|
| Impedanz / impedance | 100 MHz | Z | 40 | Ω | $\pm 25\%$ |
| Max. Impedanz / max. impedance | 1000 MHz | Z | 60 | Ω | typ. |
| DC-Widerstand / DC-resistance | | R_{DC} | 0,15 | Ω | max. |
| Nennstrom / rated current | | I_{DC} | 400 | mA | max. |
| | | | | | |

C Lötpad / soldering spec.:



D Prüfgeräte / test equipment:

HP 4396B / HP 16192A für/for Z und/and material
HP 34401 A für/for R_{DC} und/and I_{DC}

E Testbedingungen / test conditions:

Luftfeuchtigkeit / humidity: 33%
 Umgebungstemperatur / temperature: + 20°C

F Werkstoffe & Zulassungen / material & approvals:

Basismaterial / base material: Ferrit / ferrite

G Eigenschaften / general specifications:

Lagertemperatur / storage temperature: -20°C - + 60°C
 Betriebstemp. / operating temperature: -55°C - +125°C

| Freigabe erteilt / general release: | Kunde / customer | | |
|-------------------------------------|--------------------------|------|--------------------------------------|
| | | | |
| | | | |
| Datum / date | Unterschrift / signature | SSt | Update 05-12-16 |
| | | LF | IDC 05-01-10 |
| | | SST | RoHS Update 04-10-11 |
| | | LF | Update 2GHz 04-01-14 |
| Geprüft / checked | Kontrolliert / approved | Name | Änderung / modification Datum / date |

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>

Spezifikation für Freigabe / specification for release


Kunde / customer : _____
 Artikelnummer / part number : **74279260**
 Bezeichnung : **Multilayer-SMD-Ferrit**
 description : **Multilayer-SMD-Ferrite**

LF



DATUM / DATE : 2005-12-16

H typischer Impedanzverlauf / typical impedance curve:



| | | | |
|-------------------------------------|--------------------------|------|--------------------------------------|
| Freigabe erteilt / general release: | Kunde / customer | | |
| | | | |
| Datum / date | Unterschrift / signature | | SSt Update 05-12-16 |
| Geprüft / checked | Würth Elektronik | | |
| | | | LF IDC 05-01-10 |
| | | | SST RoHS Update 04-10-11 |
| | | | LF Update 2GHz 04-01-14 |
| | Kontrolliert / approved | Name | Änderung / modification Datum / date |

This electronic component is designed and developed with the intention for use in general electronics equipments. Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body. In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before use. It is essential to give consideration when to install a protective circuit at the design stage.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>