


**ELECTRICAL SPECIFICATION**

RATED VOLTAGE	440/250V
LINE FREQUENCY	50/60Hz
TEMPERATURE RANGE	-25 to 85 DegC
TEST VOLTAGE	2.0KV DC
LEAKAGE CURRENT	2.2mA AT 250V 50Hz
WEIGHT	2.7kg



**PRODUCT RANGE**

TYPE	CURRENT I(RMS) @40°C	INDUCTANCE (L)	RESISTANCE (R) PER WINDING	MINIMUM INSERTION LOSS AT 150 kHz	
				COMMON MODE	DIFFERENTIAL MODE
IHF418	18A	1.60 mH	7.40 mR	42dB	30dB
IHF425	25A	1.10 mH	4.00 mR	39dB	27dB
IHF436	36A	0.55 mH	1.65 mR	33dB	21dB
IHF450	50A	0.28 mH	1.00 mR	27dB	15dB

**ROXBURGH ELECTRONICS LTD** TITLE ELECTRICAL AND MECHANICAL SPECIFICATION

DrgNo **IHF4XX-M6-GS** ISSUE **3** GENERAL SPECIFICATION FOR IHF4XX

Sheet 1 of 1 Aprvd Date 16/07/01 Aprvd By SW Drwn by BFS SCALE N/A CNN--- Location N:\DWG\GS\GS000142

© ROXBURGH ELECTRONICS LTD, FOXHILLS INDUSTRIAL PARK, SCUNTHORPE, NORTH LINCOLNSHIRE, DN15 8QJ TEL +44 1724 281770 F +44 1724 270230