


PART NO.

7001-4P4C


REVISIONS								
ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Ramya	31/08/09	Naveen	31/08/09	Farnell	14/09/09

RoHS

Compliant



13.34 ±0.34



For flat cable

Dimensions : Millimetres

Specifications:Current rating : 1.0A ac/dc. Voltage rating : 150V ac/dc Maximum contact resistance : $20m\Omega$. Minimum insulator resistance : 1000MΩ.

: 500V ac for one minute. Withstanding voltage : -40°C to +125°C.

Operating temperature range Material and finish:

: High temperature plastic. Insulator Contact : Phosphor bronze. Plating : Gold plated.

Part Number Table


Description	Part Number				
Plug, RJ11, 4P4C, Flat	7001-4P4C				

p	TOLERANCES:	DRAWN BY:	DATE:	DRAWI	NG TITLE:						
UNLESS OTHERWISE		Ramya	31/08/09	RJ11 Modular Plug - 4P4C							
SPECIFIED,	SPECIFIED,	CHECKED BY:	DATE:	SIZE	DWG NO.		ELECTRONIC FILE				
DIMENSIONS ARE FOR REFERENCE		Naveen	31/08/09	Α		M10002362	1712384-DWG		A		
	PURPOSES ONLY.	APPROVED BY:	DATE:			Ι					
		Farnell	14/09/09	SCALE: NTS		U.O.M.: mm		SHEET: 1 OF 2			



REVISIONS PART NO. ECN # REV DESCRIPTION DRAWN CHECKD DATE APPRVD DATE 7001-4P4C Α RELEASED Ramya 31/08/09 Naveen 31/08/09 Farnell 14/09/09

Part Number Explanation:



: 4P = 4 Positions. Number of Positions **Number of Contacts** : 4C = 4 Contacts.

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

ELECTRONIC FILE

SHEET: 2

1712384-DWG

REV

Α

OF 2

TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:						
UNLESS OTHERWISE	Ramya	31/08/09]			RJ11 Modular Plug - 4P4C			
SPECIFIED,	CHECKED BY:	DATE:	SIZE	DWG NO.			ELECTRONIC F		
DIMENSIONS ARE FOR REFERENCE	Naveen 31/08/09		Δ	2	M10002362		1712384-DW		
PURPOSES ONLY.	APPROVED BY:	DATE:	\vdash						
FUNFUSES UNLT.	Farnell	14/09/09	SCALE: NTS		U.O.M.: mm		SHEET:		