

Spezifikation für Freigabe / specification for release

Kunde / customer:

Artikelnummer / part number: **744823601**

LF




Bezeichnung: **STROMKOMP. DROSSEL WE-CMB**

description: **COMMON MODE CHOKE WE-CMB**

DATUM / DATE : 2006-06-16

A Mechanische Abmessungen / dimensions




	M	
A	25,0 max.	mm
B	17,0 max.	mm
C	7,5 ± 0,5	mm
D	10,7 ± 0,5	mm
E	26,5 max.	mm
F	3,0 ± 0,5	mm
G	0,7 ref.	mm

B Elektrische Eigenschaften / electrical properties

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	tol.
Leerlauf-Induktivität inductance	10 kHz / 500µA	L _O	1,0	mH	±30%
DC-Widerstand / DC-resistance	@ 25°C	R _{DC}	13	mΩ	max.
Nennstrom / nominal current		I _{DC}	6,0	A	max.
Nennspannung / nominal voltage		U _N	250	V _{AC}	typ.

C Schaltbild / schematic:



D Prüfgeräte / test equipment

WAYNE KERR WK3260B/WK3265 für/for L₀/L_N und/and RDC
HP 34401 A für/for I_N

E Testbedingungen/ test conditions

Luftfeuchtigkeit / humidity: 33%
 Umgebungstemperatur / temperature: +25°C
 Prüfspannung / testing voltage: 1500 V, 50 Hz
 5mA , 2 sec.

F Werkstoffe & Zulassungen / material & approvals

Socket / base: UL94V-0
 Draht / wire: 2UEWF (155°C)
 Verguß / molding: UL94V-2
 Abstandhalter / spacer: UL94V-0

G Eigenschaften / general specifications

Klimabeständigkeit/ climatic class: 40/125/21
 Betriebstemp. / operating temperature: -40°C - + 125°C
 Übertemperatur / temperature rise: < 55 K
 It is recommended that the temperature of the part does not exceed 125°C under worst case operating conditions.

Freigabe erteilt / general release:	Kunde / customer		

Datum / date	Unterschrift / signature		
.....		
Geprüft / checked	Würth Elektronik		

Geprüft / checked	Kontrolliert / approved		

	Name	Änderung / modification	Datum / date
	MST	Version 6	06-06-16
	MST	Version 5	05-11-18
	MST	Version 4	04-10-11
	MST	Version 3	04-06-22
	MST	Version 2	03-12-01
	MST	Version 1	03-07-03

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 -3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>