Potentiometers



	Resistive Element	Power (watts)	Resistive Range (ohms)	Tolerance	Resistance Taper (Law)	Body Dimension	Shaft	Bushing	Terminals
PO	TENTIOMETERS		DUSTRIA	L					
470	Conductive plastic	0.5	150-5 meg	±10%, ±20%	Linear Non-Linear	15/16" dia.	Plain, Slotted Flatted Knurled 1/4" dia. Metal	Plain Locking 3/8" dia. Metal	PC Solder lug Wire-wrap
53	Conductive plastic	2.0	50-5 meg	±10%, ±20%	Linear Non-Linear	1" dia.	Plain, Slotted Flatted Knurled 1/4 " dia. Metal	Plain Locking 3/8" dia. Metal	Solder lug
	Note: 53 Series availa	able with	rotary switc	hes.					
J (RV4) (2RV7)	Carbon composition	2.25	50-5 meg	±10, ±20%	Linear Non-Linear	1.156" dia.	Plain, Slotted Flatted 1/4" dia. Metal	Plain Locking Watertight 3/8 " dia. Metal	Solder lug
	Note: J Series availab	le as Bri	dged-T, Brid	ged-H, L and S	traight-T atten	uators.	<u> </u>		
EJ									
380	Conductive plastic	2.0	Extra lon	g life version o ±10%, ±20%	f J, with single Linear Non-Linear	e or dual config	Plain, Slotted Flatted Knurled 1/4" dia. Metal	Plain Locking 3/8" dia. Metal	Solder lug
Alexander of the same of the s	Conductive plastic Note: 380 Series avai		50-5 meg	±10%, ±20%	Linear Non-Linear		Plain, Slotted Flatted Knurled 1/4" dia.	Locking 3/8" dia.	Solder lug
Alexander of the same of the s	·		50-5 meg	±10%, ±20%	Linear Non-Linear		Plain, Slotted Flatted Knurled 1/4" dia.	Locking 3/8" dia.	Solder lug Solder lug Wire wrap
380	Note: 380 Series avai	lable wit	50-5 meg h rotary switt 100-5 meg	±10%, ±20% ches. 100,000 ±10, ±20%	Linear Non-Linear cycle life. Linear Non-Linear	1" dia. 5/8" dia.	Plain, Slotted Flatted Knurled 1/4" dia. Metal Plain, Slotted Flatted Knurled 1/8" dia.	Locking 3/8" dia. Metal Plain Locking 1/4" dia.	Solder lug
380	Note: 380 Series avail	lable wit	50-5 meg h rotary switt 100-5 meg	±10%, ±20% ches. 100,000 ±10, ±20%	Linear Non-Linear cycle life. Linear Non-Linear	1" dia. 5/8" dia.	Plain, Slotted Flatted Knurled 1/4" dia. Metal Plain, Slotted Flatted Knurled 1/8" dia.	Locking 3/8" dia. Metal Plain Locking 1/4" dia.	Solder lug
381	Note: 380 Series avai Conductive plastic Note: 381 Series ava	1.0 ilable wit	50-5 meg h rotary switt 100-5 meg h rotary mon 50-5 meg	±10%, ±20% ches. 100,000 ±10, ±20% mentary and alt ±10, ±20%	Linear Non-Linear cycle life. Linear Non-Linear ernate action s	1" dia. 5/8" dia.	Plain, Slotted Flatted Knurled 1/4" dia. Metal Plain, Slotted Flatted Knurled 1/8" dia. Metal Plain, Slotted Flatted Knurled 1/8" dia.	Plain Locking 1/4" dia. Metal Plain Locking 1/4" dia. Metal	Solder lug Wire wrap

Clarostat provides Mil-spec products including, but not limited to the following units displayed in this catalog:

Industrial	Board Washable	Wirewound	Trimmer	Resistor
Series 53(RV4) Series J(RV4) Series 382(RV6), 392(RV6) G (RV6) and W(RV6)	Series 392 (RV6 & RV8) Series 382(RV6) G (RV6) W(RV6)	Series 43 (RA20) Series 58(RA30)	Series R(RJ11)	Series RW

Military