





ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS

DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1991	A	RELEASED	JN	05/15/09	JWM	05/15/09	JWW	05/15/09





Performance Specification

- Self extinguishing
- Excellent flame and moisture resistance
- Extremely small sturdy and mechanical safe
- Product Type: Wire-wound Resistor
- Power Rating: 5 Watts
- Resistance Tolerance: ±5%

Derating Curve

Heat Rise Chart



Performance Specification

- Temperature coefficient: <20Ω: ±400PPM/°C; ≥20: ±350PPM/°C
- Short-time overload: Δ R/R ≤ ±(5.0% + 0.05Ω), with no evidence of mechanical damage.
- Dielectric withstanding voltage: No evidence of flashover, mechanical damage, arcing or insulation breakdown.
- Terminal strength: No evidence of mechanical damage.
- Solderability: Min. 95% coverage
- Temperature cycling: Δ R/R ≤ ±(2.0% + 0.05Ω), with no evidence of mechanical damage.
- Humidity (Steady State): Δ R/R ≤ ±(5.0% + 0.05Ω), with no evidence of mechanical damage.
- Load life in humidity: For Wire-wound range, the Δ R/R is ±5%
For Power film range, <100KΩ, the Δ R/R is ±5%
For Power film range, ≥100KΩ, the Δ R/R is ±10%
- Load Life: For Wire-wound range, the Δ R/R is ±5%
For Power film range, <100KΩ, the Δ R/R is ±5%
For Power film range, ≥100KΩ, the Δ R/R is ±10%
- Resistance to solderability heat: Δ R/R ±(1.0% + 0.05Ω) with no evidence of mechanical damage.

Mfg. P/N	Resistance (Ohms)
MCPRW05WJW100B00	10
MCPRW05WJW10JB00	1
MCPRW05WJW150B00	15
MCPRW05WJW200B00	20
MCPRW05WJW20JB00	2
MCPRW05WJW270B00	27
MCPRW05WJW300B00	30
MCPRW05WJW30JB00	3
MCPRW05WJW330B00	33
MCPRW05WJW390B00	39
MCPRW05WJW39JB00	3.9
MCPRW05WJW430B00	43
MCPRW05WJW470B00	47
MCPRW05WJW47JB00	4.7
MCPRW05WJW68JB00	6.8

DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
Jason Nash	05/15/09
CHECKED BY:	DATE:
JWM	05/15/09
APPROVED BY:	DATE:
JWM	05/15/09

DRAWING TITLE:			
5watt (Wire-wound) Cement Fixed Resistors			
SIZE	DWG. NO.	ELECTRONIC FILE	REV
A	Ta-1181	Ta-1181.DWG	A
SCALE:	U.O.M.:	SHEET:	
NTS	INCHES	1 OF 1	