



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF26285-20B	LCD HIGH OUTPUT WHITE 5600°k RGB	1700 @ 0°C	725	5	30,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
				TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP			
A	CIRCUIT VOLTS & BRIGHTNESS CHNG-CONVERT TO CAD DRAWING	5/18/01	DRAWN BY L. WENGSTROM	APPV'D BY DATE FD 5/18/01	SIZE A	FSCM NO. 55335	DRAWING NO. BF26285-20B
RELEASED		4/13/99	- CAD DRAWING -		SCALE NONE	RELEASED DATE 4/13/99	REVISION DATE 5/18/01
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	MANUAL REVISIONS NOT PERMITTED			REV. NO. A	SHEET 1 OF 1