



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS)
BF2261-24B	LCD HIGH OUTPUT WHITE 8400°K RGB	680 @ 0°C	235	5	38,000 ± 10%	10,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>THIRD ANGLE PROJECTION</p>			<p>METRIC</p> <p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0.2</p> <p>2 PL +/- 0</p> <p>ANGLE +/- 0</p>		<p><b>JKL</b> COMPONENTS CORPORATION</p>					
<p>DRAWN BY</p> <p>L. WENGSTROM</p>			<p>APPV'D BY DATE</p> <p>F.D. 2/21/02</p>		<p>SIZE</p> <p><b>A</b></p>		<p>FSCM NO.</p> <p><b>55335</b></p>		<p>DRAWING NO.</p> <p><b>BF2261-24B</b></p>	
<p>RELEASED</p>			<p>2/21/02</p>		<p>SCALE</p> <p>NONE</p>		<p>RELEASED DATE</p> <p>2/21/02</p>		<p>REVISION DATE</p>	
<p>REV. NO.</p>			<p>DESCRIPTION/ECO NUMBER</p>		<p>APPV'D DATE</p>		<p>- CAD DRAWING -</p> <p>MANUAL REVISIONS NOT PERMITTED</p>		<p>REV. NO.</p>	
									<p>SHEET</p> <p>1 OF 1</p>	