



JKL PART NUMBER	LENGTH A +/- 2mm	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF650-20B	50mm	RGB	390	170	5 ± 1	6,500 ± 650	20,000
BF6100-20B	100mm		500	200	5 ± 1	6,500 ± 650	20,000
BF6120-20B	120mm	HIGH	590	235	5 ± 1	6,500 ± 650	20,000
BF6144-20B	144mm	OUTPUT	600	240	5 ± 1	6,500 ± 650	20,000
BF6150-20B	150mm	WHITE	615	245	5 ± 1	6,500 ± 650	20,000
BF6165-20B	165mm	5400°	640	255	5 ± 1	6,500 ± 650	20,000
BF6178-20B	178mm	KELVIN	675	270	5 ± 1	6,500 ± 650	20,000
BF6200-20B	200mm	(REF.)	725	290	5 ± 1	6,500 ± 650	20,000
BF6225-20B	220mm		825	330	5 ± 1	6,500 ± 650	20,000
BF6333-20B	333mm		1125	450	5 ± 1	6,500 ± 650	20,000

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>			
DRAWN BY L. WENGSTROM		APPV'D BY DATE JK 02/29/00		SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF 6-20B</b>	
TITLE SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 2/29/00	REVISION DATE	
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	RELEASED DATE 2/29/00	REVISION DATE	REV. NO.	SHEET 1 OF 1	